

## TEST REPORT

### IEC 62471

### Photobiological safety of lamps and lamp systems

Report Number ..... : FTS26ER-02114L

Tested by

(name + signature) ..... : Tim Huang

*Tim Huang*

Reviewed by

(name + signature) ..... : Bain Ye

Date of issue ..... : 29 May 2026

Total number of pages ..... : 19 pages

Name of Testing Laboratory

preparing the Report ..... : Guangdong Future Test Services Co., Ltd.

Applicant's name ..... : Mid Ocean Brands B.V.

Address ..... : Unit 711-716, 7/F., Tower A, 83 King Lam Street, Cheung Sha Wan,  
Kowloon, Hong Kong.

Test specification ..... :

Standard ..... : EN 62471:2008

Test procedure ..... : Commission test

Non-standard test method ..... : N/A

Test Report Form No. .... : TRF-LT0007-V01

Test Report Form(s) Originator .... : FTS

Master TRF ..... : 2025-03-15

This publication may be produced in whole or in part for non-commercial purposes as long as FTS is acknowledged as copyright owner and source of the material. FTS takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context

Test item description ..... : Christmas Ornament With Light

Trade Mark ..... : —

Manufacturer ..... : Mid Ocean Brands B.V.

Address ..... : Unit 711-716, 7/F., Tower A, 83 King Lam Street, Cheung Sha Wan,  
Kowloon, Hong Kong.

Model/Type reference ..... : CX1558

Ratings ..... : Input: DC4.5V

|                                                                                                                                                                                                                                                |                                                                                                                                                                    |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>List of Attachments (including a total number of pages in each attachment):</b>                                                                                                                                                             |                                                                                                                                                                    |
| ANNEX 1: Test result in graphical presentation                                                                                                                                                                                                 | Pages 15 to 17                                                                                                                                                     |
| ANNEX 2: Photo document                                                                                                                                                                                                                        | Pages 18 fo 19                                                                                                                                                     |
| <b>Summary of testing:</b><br>The product's have been tested according to standard EN 62471:2008 and found in compliance <b>Risk Group 1(Low-Risk)</b> .                                                                                       |                                                                                                                                                                    |
| <b>Tests performed (name of test and test clause):</b><br>The test samples meet the requirements of related standards and all tests are carried out                                                                                            | <b>Testing location:</b><br><b>Guangdong Future Test Services Co., Ltd.</b><br>Room A01, A02, A03, No.228, Min'an South Road, Xiaolan, Zhongshan, Guangdong, China |
| <b>Summary of compliance with National Differences (List of countries addressed):</b><br>Requirement of EU Group DIFFERENCES, UK<br><input checked="" type="checkbox"/> The product fulfils the requirements of <b>EN 62471:2008</b>           |                                                                                                                                                                    |
| <b>Copy of marking plate:</b><br>The artwork below may be only a draft. The use of certification marks on a product must be authorized by the respective NCBs that own these marks.<br><div style="text-align: center; height: 200px;">/</div> |                                                                                                                                                                    |

|                                                                                                                                                                                                                                                                                                                                            |                                                                                                                                                                                                                           |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>DESCRIPTION</b> ..... :                                                                                                                                                                                                                                                                                                                 |                                                                                                                                                                                                                           |
| Type of appliance..... :                                                                                                                                                                                                                                                                                                                   | Christnas Ornament With Light                                                                                                                                                                                             |
| Type / model..... :                                                                                                                                                                                                                                                                                                                        | CX1558                                                                                                                                                                                                                    |
| Tested lamp..... :                                                                                                                                                                                                                                                                                                                         | <input checked="" type="checkbox"/> continuous wave lamps <input type="checkbox"/> pulsed lamps                                                                                                                           |
| Lamp classification group .....                                                                                                                                                                                                                                                                                                            | <input type="checkbox"/> Except Group(Exempt)<br><input checked="" type="checkbox"/> Risk Group 1(Low-Risk)<br><input type="checkbox"/> Risk Group 2 (Moderate-Risk)<br><input type="checkbox"/> Risk Group 3 (High-Risk) |
| Bulb..... :                                                                                                                                                                                                                                                                                                                                | --                                                                                                                                                                                                                        |
| Classification of installation and use..... :                                                                                                                                                                                                                                                                                              | Class III                                                                                                                                                                                                                 |
| Supply Connection..... :                                                                                                                                                                                                                                                                                                                   | DC4.5V                                                                                                                                                                                                                    |
| Rated of the lamp..... :                                                                                                                                                                                                                                                                                                                   | --                                                                                                                                                                                                                        |
| Used measurement instrument .....                                                                                                                                                                                                                                                                                                          | EVERFINE OST-500 system                                                                                                                                                                                                   |
| Notes .....                                                                                                                                                                                                                                                                                                                                | --                                                                                                                                                                                                                        |
| Possible test case verdicts:                                                                                                                                                                                                                                                                                                               |                                                                                                                                                                                                                           |
| -- test case does not apply to the test object..... : N/A<br>-- test object does meet the requirement .....                                                                                                                                                                                                                                |                                                                                                                                                                                                                           |
| -- test object does not meet the requirement .....                                                                                                                                                                                                                                                                                         |                                                                                                                                                                                                                           |
| -- P (Pass)<br>-- F (Fail)                                                                                                                                                                                                                                                                                                                 |                                                                                                                                                                                                                           |
| Testing:                                                                                                                                                                                                                                                                                                                                   |                                                                                                                                                                                                                           |
| Date of receipt of test item .....                                                                                                                                                                                                                                                                                                         | 2026-05-13                                                                                                                                                                                                                |
| Date (s) of performance of tests .....                                                                                                                                                                                                                                                                                                     | 2026-05-16                                                                                                                                                                                                                |
| <b>General remarks:</b>                                                                                                                                                                                                                                                                                                                    |                                                                                                                                                                                                                           |
| "(See Enclosure #)" refers to additional information appended to the report.<br>"(See appended table)" refers to a table appended to the report.<br>Throughout this report a <input checked="" type="checkbox"/> comma / <input type="checkbox"/> point is used as the decimal separator.<br>For European group deviation, see attachment. |                                                                                                                                                                                                                           |
| <b>Manufacturer's Declaration per sub-clause 4.2.5 of IECCE 02:</b>                                                                                                                                                                                                                                                                        |                                                                                                                                                                                                                           |
| The application for obtaining a CB Test Certificate includes more than one factory location and a declaration from the Manufacturer stating that the sample(s) submitted for evaluation is (are) representative of the products from each factory has been provided..... :                                                                 | <input type="checkbox"/> Yes<br><input checked="" type="checkbox"/> Not applicable                                                                                                                                        |
| <b>Name and address of factory (ies)..... :</b> Same as manufacturer                                                                                                                                                                                                                                                                       |                                                                                                                                                                                                                           |
| <b>General product information:</b>                                                                                                                                                                                                                                                                                                        |                                                                                                                                                                                                                           |
| 1. This product is Christnas Ornament With Light, model number: CX1558.                                                                                                                                                                                                                                                                    |                                                                                                                                                                                                                           |

| IEC 62471 |                                                                                                                                                                                                                                                                                                                                                                |                         |            |
|-----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------|
| Clause    | Requirement + Test                                                                                                                                                                                                                                                                                                                                             |                         | Verdict    |
| <b>4</b>  | <b>EXPOSURE LIMITS</b>                                                                                                                                                                                                                                                                                                                                         |                         | <b>P</b>   |
| 4.1       | General                                                                                                                                                                                                                                                                                                                                                        |                         | <b>P</b>   |
|           | The exposure limits in this standard is not less than 0,01 ms and not more than any 8-hour period and should be used as guides in the control of exposure                                                                                                                                                                                                      |                         | <b>P</b>   |
|           | Detailed spectral data of a light source are generally required only if the luminance of the source exceeds $10^4 \text{ cd}\cdot\text{m}^{-2}$                                                                                                                                                                                                                | see clause 4.3          | <b>N/A</b> |
| 4.3       | Hazard exposure limits                                                                                                                                                                                                                                                                                                                                         |                         | <b>P</b>   |
| 4.3.1     | Actinic UV hazard exposure limit for the skin and eye                                                                                                                                                                                                                                                                                                          |                         | <b>P</b>   |
|           | The exposure limit for effective radiant exposure is $30 \text{ J}\cdot\text{m}^{-2}$ within any 8-hour period                                                                                                                                                                                                                                                 |                         | <b>P</b>   |
|           | To protect against injury of the eye or skin from ultraviolet radiation exposure produced by a broadband source, the effective integrated spectral irradiance, $E_s$ , of the light source shall not exceed the levels defined by:                                                                                                                             |                         | <b>P</b>   |
|           | $E_s \cdot t = \sum_{200}^{400} \sum_t E_\lambda(\lambda, t) \cdot S_{UV}(\lambda) \cdot \Delta t \cdot \Delta \lambda \leq 30 \quad \text{J}\cdot\text{m}^{-2}$                                                                                                                                                                                               |                         | <b>P</b>   |
|           | The permissible time for exposure to ultraviolet radiation incident upon the unprotected eye or skin shall be computed by:                                                                                                                                                                                                                                     |                         | <b>P</b>   |
|           | $t_{\max} = \frac{30}{E_s} \quad \text{s}$                                                                                                                                                                                                                                                                                                                     |                         | <b>P</b>   |
| 4.3.2     | Near-UV hazard exposure limit for eye                                                                                                                                                                                                                                                                                                                          |                         | <b>P</b>   |
|           | For the spectral region 315 nm to 400 nm (UV-A) the total radiant exposure to the eye shall not exceed $10000 \text{ J}\cdot\text{m}^{-2}$ for exposure times less than 1000 s. For exposure times greater than 1000 s (approximately 16 minutes) the UV-A irradiance for the unprotected eye, $E_{UVA}$ , shall not exceed $10 \text{ W}\cdot\text{m}^{-2}$ . |                         | <b>P</b>   |
|           | $E_{UVA} \cdot t = \sum_{315}^{400} \sum_t E_\lambda(\lambda, t) \cdot \Delta t \cdot \Delta \lambda \leq 10000 \quad \text{J}\cdot\text{m}^{-2}$                                                                                                                                                                                                              | $t < 1000 \text{ s}$    | <b>N/A</b> |
|           | $E_{UVA} \leq 10 \quad \text{W}\cdot\text{m}^{-2}$                                                                                                                                                                                                                                                                                                             | $t \geq 1000 \text{ s}$ | <b>P</b>   |
|           | The permissible time for exposure to ultraviolet radiation incident upon the unprotected eye for time less than 1000 s, shall be computed by:                                                                                                                                                                                                                  |                         | <b>N/A</b> |
|           | $t_{\max} \leq \frac{10000}{E_{UVA}} \quad \text{s}$                                                                                                                                                                                                                                                                                                           |                         | <b>N/A</b> |
| 4.3.3     | Retinal blue light hazard exposure limit                                                                                                                                                                                                                                                                                                                       |                         | <b>P</b>   |
|           | To protect against retinal photochemical injury from chronic blue-light exposure, the integrated spectral radiance of the light source weighted against the blue-light hazard function, $B(\lambda)$ , i.e., the blue-light weighted radiance, $L_B$ , shall not exceed the levels defined by:                                                                 | see table 4.2           | <b>P</b>   |

| IEC 62471 |                                                                                                                                                                                                                                                                                              |                                                      |         |
|-----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------|---------|
| Clause    | Requirement + Test                                                                                                                                                                                                                                                                           | Result – Remark                                      | Verdict |
|           | $L_B \cdot t = \sum_{300}^{700} \sum_t L_\lambda(\lambda, t) \cdot B(\lambda) \cdot \Delta\lambda \leq 10^6 \text{ J} \cdot \text{m}^{-2} \cdot \text{sr}^{-1}$                                                                                                                              | for $t \leq 10^4$ s<br>$t_{\max} = \frac{10^6}{L_B}$ | N/A     |
|           | $L_B = \sum_{300}^{700} L_\lambda \cdot B(\lambda) \cdot \Delta\lambda \leq 100 \text{ W} \cdot \text{m}^{-2} \cdot \text{sr}^{-1}$                                                                                                                                                          | for $t > 10^4$ s                                     | P       |
| 4.3.4     | Retinal blue light hazard exposure limit - small source                                                                                                                                                                                                                                      |                                                      | N/A     |
|           | Thus the spectral irradiance at the eye $E_\lambda$ , weighted against the blue-light hazard function $B(\lambda)$ shall not exceed the levels defined by:                                                                                                                                   |                                                      | N/A     |
|           | $E_B \cdot t = \sum_{300}^{700} \sum_t E_\lambda(\lambda, t) \cdot B(\lambda) \cdot \Delta\lambda \leq 100 \text{ J} \cdot \text{m}^{-2}$                                                                                                                                                    | for $t \leq 100$ s<br>$t_{\max} = \frac{100}{E_B}$   | N/A     |
|           | $E_B = \sum_{300}^{700} E_\lambda \cdot B(\lambda) \cdot \Delta\lambda \leq 1 \text{ W} \cdot \text{m}^{-2}$                                                                                                                                                                                 | for $t > 100$ s                                      | N/A     |
| 4.3.5     | Retinal thermal hazard exposure limit                                                                                                                                                                                                                                                        |                                                      | P       |
|           | To protect against retinal thermal injury, the integrated spectral radiance of the light source, $L_\lambda$ , weighted by the burn hazard weighting function $R(\lambda)$ (from Figure 4.2 and Table 4.2), i.e., the burn hazard weighted radiance, shall not exceed the levels defined by: |                                                      | P       |
|           | $L_R = \sum_{380}^{1400} L_\lambda \cdot R(\lambda) \cdot \Delta\lambda \leq \frac{50000}{\alpha \cdot t^{0.25}} \text{ W} \cdot \text{m}^{-2} \cdot \text{sr}^{-1}$                                                                                                                         | $10 \mu\text{s} \leq t \leq 10 \text{ s}$            | P       |
| 4.3.6     | Retinal thermal hazard exposure limit – weak visual stimulus                                                                                                                                                                                                                                 |                                                      | P       |
|           | For an infrared heat lamp or any near-infrared source where a weak visual stimulus is inadequate to activate the aversion response, the near infrared (780 nm to 1400 nm) radiance, $L_{IR}$ , as viewed by the eye for exposure times greater than 10 s shall be limited to:                |                                                      | P       |
|           | $L_{IR} = \sum_{780}^{1400} L_\lambda \cdot R(\lambda) \cdot \Delta\lambda \leq \frac{6000}{\alpha} \text{ W} \cdot \text{m}^{-2} \cdot \text{sr}^{-1}$                                                                                                                                      | $t > 10 \text{ s}$                                   | P       |
| 4.3.7     | Infrared radiation hazard exposure limits for the eye                                                                                                                                                                                                                                        |                                                      | P       |
|           | The avoid thermal injury of the cornea and possible delayed effects upon the lens of the eye (cataractogenesis), ocular exposure to infrared radiation, $E_{IR}$ , over the wavelength range 780 nm to 3000 nm, for times less than 1000 s, shall not exceed:                                |                                                      | N/A     |
|           | $E_{IR} = \sum_{780}^{3000} E_\lambda \cdot \Delta\lambda \leq 18000 \cdot t^{-0.75} \text{ W} \cdot \text{m}^{-2}$                                                                                                                                                                          | $t \leq 1000 \text{ s}$                              | N/A     |
|           | For times greater than 1000 s the limit becomes:                                                                                                                                                                                                                                             |                                                      | P       |
|           | $E_{IR} = \sum_{780}^{3000} E_\lambda \cdot \Delta\lambda \leq 100 \text{ W} \cdot \text{m}^{-2}$                                                                                                                                                                                            | $t > 1000 \text{ s}$                                 | P       |
| 4.3.8     | Thermal hazard exposure limit for the skin                                                                                                                                                                                                                                                   |                                                      | P       |

| IEC 62471 |                                                                                                                                                                            |                                        |         |
|-----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------|---------|
| Clause    | Requirement + Test                                                                                                                                                         | Result – Remark                        | Verdict |
|           | Visible and infrared radiant exposure (380 nm to 3000 nm) of the skin shall be limited to:                                                                                 |                                        | N/A     |
|           | $E_H \cdot t = \sum_{380}^{3000} E_{\lambda}(\lambda, t) \cdot \Delta\lambda \leq 20000 \cdot t^{0.25} \quad \text{J} \cdot \text{m}^{-2}$                                 | $t \leq 10 \text{ s}$                  | N/A     |
| <b>5</b>  | <b>MEASUREMENT OF LAMPS AND LAMP SYSTEMS</b>                                                                                                                               |                                        | P       |
| 5.1       | Measurement conditions                                                                                                                                                     |                                        | P       |
|           | Measurement conditions shall be reported as part of the evaluation against the exposure limits and the assignment of risk classification.                                  |                                        | P       |
| 5.1.1     | Lamp ageing (seasoning)                                                                                                                                                    |                                        | P       |
|           | Seasoning of lamps shall be done as stated in the appropriate IEC lamp standard.                                                                                           |                                        | N/A     |
| 5.1.2     | Test environment                                                                                                                                                           | 1. Dark room<br>2. Temperature: 25.0°C | P       |
|           | For specific test conditions, see the appropriate IEC lamp standard or in absence of such standards, the appropriate national standards or manufacturer's recommendations. |                                        | N/A     |
| 5.1.3     | Extraneous radiation                                                                                                                                                       |                                        | P       |
|           | Careful checks should be made to ensure that extraneous sources of radiation and reflections do not add significantly to the measurement results.                          |                                        | P       |
| 5.1.4     | Lamp operation                                                                                                                                                             |                                        | N/A     |
|           | Operation of the test lamp shall be provided in accordance with:                                                                                                           |                                        | N/A     |
|           | – the appropriate IEC lamp standard, or                                                                                                                                    |                                        | N/A     |
|           | – the manufacturer's recommendation                                                                                                                                        |                                        | N/A     |
| 5.1.5     | Lamp system operation                                                                                                                                                      |                                        | P       |
|           | The power source for operation of the test lamp shall be provided in accordance with:                                                                                      |                                        | P       |
|           | – the appropriate IEC standard, or                                                                                                                                         |                                        | P       |
|           | – the manufacturer's recommendation                                                                                                                                        |                                        | N/A     |
| 5.2       | Measurement procedure                                                                                                                                                      |                                        | P       |
| 5.2.1     | Irradiance measurements                                                                                                                                                    |                                        | P       |
|           | Minimum aperture diameter 7mm.                                                                                                                                             |                                        | P       |
|           | Maximum aperture diameter 50 mm.                                                                                                                                           |                                        | P       |
|           | The measurement shall be made in that position of the beam giving the maximum reading.                                                                                     |                                        | P       |
|           | The measurement instrument is adequate calibrated.                                                                                                                         |                                        | P       |
| 5.2.2     | Radiance measurements                                                                                                                                                      |                                        | P       |

| IEC 62471 |                                                                                                                                                                                                                               |                         |         |
|-----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|---------|
| Clause    | Requirement + Test                                                                                                                                                                                                            | Result – Remark         | Verdict |
| 5.2.2.1   | Standard method                                                                                                                                                                                                               |                         | P       |
|           | The measurements made with an optical system.                                                                                                                                                                                 |                         | P       |
|           | The instrument shall be calibrated to read in absolute radiant power per unit receiving area and per unit solid angle to acceptance averaged over the field of view of the instrument.                                        |                         | P       |
| 5.2.2.2   | Alternative method                                                                                                                                                                                                            |                         | N/A     |
|           | Alternatively to an imaging radiance set-up, an irradiance measurement set-up with a circular field stop placed at the source can be used to perform radiance measurements.                                                   |                         | N/A     |
| 5.2.3     | Measurement of source size                                                                                                                                                                                                    |                         | P       |
|           | The determination of $\alpha$ , the angle subtended by a source, requires the determination of the 50% emission points of the source.                                                                                         | $\alpha=0,0105$ rad     | P       |
| 5.2.4     | Pulse width measurement for pulsed sources                                                                                                                                                                                    |                         | N/A     |
|           | The determination of $\Delta t$ , the nominal pulse duration of a source, requires the determination of the time during which the emission is > 50% of its peak value.                                                        |                         | N/A     |
| 5.3       | Analysis methods                                                                                                                                                                                                              |                         | P       |
| 5.3.1     | Weighting curve interpolations                                                                                                                                                                                                |                         | P       |
|           | To standardize interpolated values, use linear interpolation on the log of given values to obtain intermediate points at the wavelength intervals desired.                                                                    | see table 4.1           | P       |
| 5.3.2     | Calculations                                                                                                                                                                                                                  |                         | P       |
|           | The calculation of source hazard values shall be performed by weighting the spectral scan by the appropriate function and calculating the total weighted energy.                                                              |                         | P       |
| 5.3.3     | Measurement uncertainty                                                                                                                                                                                                       |                         | P       |
|           | The quality of all measurement results must be quantified by an analysis of the uncertainty.                                                                                                                                  | see Annex C in the norm | P       |
| <b>6</b>  | <b>LAMP CLASSIFICATION</b>                                                                                                                                                                                                    |                         | P       |
|           | For the purposes of this standard it was decided that the values shall be reported as follows:                                                                                                                                | see table 6.1           | P       |
|           | – for lamps intended for general lighting service, the hazard values shall be reported as either irradiance or radiance values at a distance which produces an illuminance of 500 lux, but not at a distance less than 200 mm |                         | N/A     |
|           | – for all other light sources, including pulsed lamp sources, the hazard values shall be reported at a distance of 200 mm                                                                                                     |                         | P       |
| 6.1       | Continuous wave lamps                                                                                                                                                                                                         |                         | P       |
| 6.1.1     | Except Group                                                                                                                                                                                                                  |                         | P       |

| IEC 62471 |                                                                                                                                                                    |                 |         |
|-----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|---------|
| Clause    | Requirement + Test                                                                                                                                                 | Result – Remark | Verdict |
|           | In the except group are lamps, which does not pose any photobiological hazard. The requirement is met by any lamp that does not pose:                              |                 | P       |
|           | – an actinic ultraviolet hazard ( $E_S$ ) within 8-hours exposure (30000 s), nor                                                                                   |                 | P       |
|           | – a near-UV hazard ( $E_{UVA}$ ) within 1000 s, (about 16 min), nor                                                                                                |                 | P       |
|           | – a retinal blue-light hazard ( $L_B$ ) within 10000 s (about 2,8 h), nor                                                                                          |                 | P       |
|           | – a retinal thermal hazard ( $L_R$ ) within 10 s, nor                                                                                                              |                 | P       |
|           | – an infrared radiation hazard for the eye ( $E_{IR}$ ) within 1000 s                                                                                              |                 | P       |
| 6.1.2     | Risk Group 1 (Low-Risk)                                                                                                                                            |                 | N/A     |
|           | In this group are lamps, which exceeds the limits for the except group but that does not pose:                                                                     |                 | N/A     |
|           | – an actinic ultraviolet hazard ( $E_S$ ) within 10000 s, nor                                                                                                      |                 | N/A     |
|           | – a near ultraviolet hazard ( $E_{UVA}$ ) within 300 s, nor                                                                                                        |                 | N/A     |
|           | – a retinal blue-light hazard ( $L_B$ ) within 100 s, nor                                                                                                          |                 | N/A     |
|           | – a retinal thermal hazard ( $L_R$ ) within 10 s, nor                                                                                                              |                 | N/A     |
|           | – an infrared radiation hazard for the eye ( $E_{IR}$ ) within 100 s                                                                                               |                 | N/A     |
|           | Lamps that emit infrared radiation without a strong visual stimulus and do not pose a near-infrared retinal hazard ( $L_{IR}$ ), within 100 s are in Risk Group 1. |                 | N/A     |
| 6.1.3     | Risk Group 2 (Moderate-Risk)                                                                                                                                       |                 | N/A     |
|           | This requirement is met by any lamp that exceeds the limits for Risk Group 1, but that does not pose:                                                              |                 | N/A     |
|           | – an actinic ultraviolet hazard ( $E_S$ ) within 1000 s exposure, nor                                                                                              |                 | N/A     |
|           | – a near ultraviolet hazard ( $E_{UVA}$ ) within 100 s, nor                                                                                                        |                 | N/A     |
|           | – a retinal blue-light hazard ( $L_B$ ) within 0,25 s (aversion response), nor                                                                                     |                 | N/A     |
|           | – a retinal thermal hazard ( $L_R$ ) within 0,25 s (aversion response), nor                                                                                        |                 | N/A     |
|           | – an infrared radiation hazard for the eye ( $E_{IR}$ ) within 10 s                                                                                                |                 | N/A     |
|           | Lamps that emit infrared radiation without a strong visual stimulus and do not pose a near-infrared retinal hazard ( $L_{IR}$ ), within 10 s are in Risk Group 2.  |                 | N/A     |
| 6.1.4     | Risk Group 3 (High-Risk)                                                                                                                                           |                 | N/A     |
|           | Lamps which exceed the limits for Risk Group 2 are in Group 3.                                                                                                     |                 | N/A     |
| 6.2       | Pulsed lamps                                                                                                                                                       |                 | N/A     |
|           | Pulse lamp criteria shall apply to a single pulse and to any group of pulses within 0,25 s.                                                                        |                 | N/A     |

| IEC 62471 |                                                                                                                                                                                                                                                          |                 |         |
|-----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|---------|
| Clause    | Requirement + Test                                                                                                                                                                                                                                       | Result – Remark | Verdict |
|           | A pulsed lamp shall be evaluated at the highest nominal energy loading as specified by the manufacturer.                                                                                                                                                 |                 | N/A     |
|           | The risk group determination of the lamp being tested shall be made as follows:                                                                                                                                                                          |                 | N/A     |
|           | – a lamp that exceeds the exposure limit shall be classified as belonging to Risk Group 3 (High-Risk)                                                                                                                                                    |                 | N/A     |
|           | – for single pulsed lamps, a lamp whose weighted radiant exposure or weighted radiance does is below the EL shall be classified as belonging to the Exempt Group                                                                                         |                 | N/A     |
|           | – for repetitively pulsed lamps, a lamp whose weighted radiant exposure or weighted radiance dose is below the EL, shall be evaluated using the continuous wave risk criteria discussed in clause 6.1, using time averaged values of the pulsed emission |                 | N/A     |

| IEC 62471                                                                                                                                     |                                                                                |                              |                                         |
|-----------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------|------------------------------|-----------------------------------------|
| Clause                                                                                                                                        | Requirement + Test                                                             |                              | Verdict                                 |
| <b>Table 4.1</b>                                                                                                                              | Spectral weighting function for assessing ultraviolet hazards for skin and eye |                              | P                                       |
| Wavelength <sup>1</sup><br>$\lambda$ , nm                                                                                                     | UV hazard function<br>$S_{uv}(\lambda)$                                        | Wavelength<br>$\lambda$ , nm | UV hazard function<br>$S_{uv}(\lambda)$ |
| 200                                                                                                                                           | 0,030                                                                          | 313*                         | 0,006                                   |
| 205                                                                                                                                           | 0,051                                                                          | 315                          | 0,003                                   |
| 210                                                                                                                                           | 0,075                                                                          | 316                          | 0,0024                                  |
| 215                                                                                                                                           | 0,095                                                                          | 317                          | 0,0020                                  |
| 220                                                                                                                                           | 0,120                                                                          | 318                          | 0,0016                                  |
| 225                                                                                                                                           | 0,150                                                                          | 319                          | 0,0012                                  |
| 230                                                                                                                                           | 0,190                                                                          | 320                          | 0,0010                                  |
| 235                                                                                                                                           | 0,240                                                                          | 322                          | 0,00067                                 |
| 240                                                                                                                                           | 0,300                                                                          | 323                          | 0,00054                                 |
| 245                                                                                                                                           | 0,360                                                                          | 325                          | 0,00050                                 |
| 250                                                                                                                                           | 0,430                                                                          | 328                          | 0,00044                                 |
| 254*                                                                                                                                          | 0,500                                                                          | 330                          | 0,00041                                 |
| 255                                                                                                                                           | 0,520                                                                          | 333*                         | 0,00037                                 |
| 260                                                                                                                                           | 0,650                                                                          | 335                          | 0,00034                                 |
| 265                                                                                                                                           | 0,810                                                                          | 340                          | 0,00028                                 |
| 270                                                                                                                                           | 1,000                                                                          | 345                          | 0,00024                                 |
| 275                                                                                                                                           | 0,960                                                                          | 350                          | 0,00020                                 |
| 280*                                                                                                                                          | 0,880                                                                          | 355                          | 0,00016                                 |
| 285                                                                                                                                           | 0,770                                                                          | 360                          | 0,00013                                 |
| 290                                                                                                                                           | 0,640                                                                          | 365*                         | 0,00011                                 |
| 295                                                                                                                                           | 0,540                                                                          | 370                          | 0,000093                                |
| 297*                                                                                                                                          | 0,460                                                                          | 375                          | 0,000077                                |
| 300                                                                                                                                           | 0,300                                                                          | 380                          | 0,000064                                |
| 303*                                                                                                                                          | 0,120                                                                          | 385                          | 0,000053                                |
| 305                                                                                                                                           | 0,060                                                                          | 390                          | 0,000044                                |
| 308                                                                                                                                           | 0,026                                                                          | 395                          | 0,000036                                |
| 310                                                                                                                                           | 0,015                                                                          | 400                          | 0,000030                                |
| <sup>1</sup> Wavelengths chosen are representative: other values should be obtained by logarithmic interpolation at intermediate wavelengths. |                                                                                |                              |                                         |
| * Emission lines of a mercury discharge spectrum.                                                                                             |                                                                                |                              |                                         |

| IEC 62471        |                                                                                           |                                         |         |
|------------------|-------------------------------------------------------------------------------------------|-----------------------------------------|---------|
| Clause           | Requirement + Test                                                                        |                                         | Verdict |
| <b>Table 4.2</b> | Spectral weighting functions for assessing retinal hazards from broadband optical sources |                                         | P       |
| Wavelength<br>nm | Blue-light hazard function<br>B ( $\lambda$ )                                             | Burn hazard function<br>R ( $\lambda$ ) |         |
| 300              | 0,01                                                                                      |                                         |         |
| 305              | 0,01                                                                                      |                                         |         |
| 310              | 0,01                                                                                      |                                         |         |
| 315              | 0,01                                                                                      |                                         |         |
| 320              | 0,01                                                                                      |                                         |         |
| 325              | 0,01                                                                                      |                                         |         |
| 330              | 0,01                                                                                      |                                         |         |
| 335              | 0,01                                                                                      |                                         |         |
| 340              | 0,01                                                                                      |                                         |         |
| 345              | 0,01                                                                                      |                                         |         |
| 350              | 0,01                                                                                      |                                         |         |
| 355              | 0,01                                                                                      |                                         |         |
| 360              | 0,01                                                                                      |                                         |         |
| 365              | 0,01                                                                                      |                                         |         |
| 370              | 0,01                                                                                      |                                         |         |
| 375              | 0,01                                                                                      |                                         |         |
| 380              | 0,01                                                                                      | 0,1                                     |         |
| 385              | 0,013                                                                                     | 0,13                                    |         |
| 390              | 0,025                                                                                     | 0,25                                    |         |
| 395              | 0,05                                                                                      | 0,5                                     |         |
| 400              | 0,10                                                                                      | 1,0                                     |         |
| 405              | 0,20                                                                                      | 2,0                                     |         |
| 410              | 0,40                                                                                      | 4,0                                     |         |
| 415              | 0,80                                                                                      | 8,0                                     |         |
| 420              | 0,90                                                                                      | 9,0                                     |         |
| 425              | 0,95                                                                                      | 9,5                                     |         |
| 430              | 0,98                                                                                      | 9,8                                     |         |
| 435              | 1,00                                                                                      | 10,0                                    |         |
| 440              | 1,00                                                                                      | 10,0                                    |         |
| 445              | 0,97                                                                                      | 9,7                                     |         |
| 450              | 0,94                                                                                      | 9,4                                     |         |
| 455              | 0,90                                                                                      | 9,0                                     |         |
| 460              | 0,80                                                                                      | 8,0                                     |         |
| 465              | 0,70                                                                                      | 7,0                                     |         |
| 470              | 0,62                                                                                      | 6,2                                     |         |
| 475              | 0,55                                                                                      | 5,5                                     |         |
| 480              | 0,45                                                                                      | 4,5                                     |         |
| 485              | 0,40                                                                                      | 4,0                                     |         |
| 490              | 0,22                                                                                      | 2,2                                     |         |

| IEC 62471        |                                                                                           |                                     |         |
|------------------|-------------------------------------------------------------------------------------------|-------------------------------------|---------|
| Clause           | Requirement + Test                                                                        |                                     | Verdict |
| <b>Table 4.2</b> | Spectral weighting functions for assessing retinal hazards from broadband optical sources |                                     | P       |
| Wavelength<br>nm | Blue-light hazard function<br>B (λ)                                                       | Burn hazard function<br>R (λ)       |         |
| 495              | 0,16                                                                                      | 1,6                                 |         |
| 500-600          | $10^{[(450-\lambda)/50]}$                                                                 | 1,0                                 |         |
| 600-700          | 0,001                                                                                     | 1,0                                 |         |
| 700-1050         |                                                                                           | $10^{[(700-\lambda)/500]}$          |         |
| 1050-1150        |                                                                                           | 0,2                                 |         |
| 1150-1200        |                                                                                           | $0,2 \cdot 10^{0,02(1150-\lambda)}$ |         |
| 1200-1400        |                                                                                           | 0,02                                |         |

| <b>Table 5.4</b>        | Summary of the ELs for the surface of the skin or cornea (irradiance based values) |                     |                         |                             |                                                     | P |
|-------------------------|------------------------------------------------------------------------------------|---------------------|-------------------------|-----------------------------|-----------------------------------------------------|---|
| Hazard Name             | Relevant equation                                                                  | Wavelength range nm | Exposure duration sec   | Limiting aperture rad (deg) | EL in terms of constant irradiance $W \cdot m^{-2}$ |   |
| Actinic UV skin & eye   | $E_S = \sum E_\lambda \cdot S(\lambda) \cdot \Delta\lambda$                        | 200 – 400           | < 30000                 | 1,4 (80)                    | 30/t                                                |   |
| Eye UV-A                | $E_{UVA} = \sum E_\lambda \cdot \Delta\lambda$                                     | 315 – 400           | $\leq 1000$<br>$> 1000$ | 1,4 (80)                    | 10000/t<br>10                                       |   |
| Blue-light small source | $E_B = \sum E_\lambda \cdot B(\lambda) \cdot \Delta\lambda$                        | 300 – 700           | $\leq 100$<br>$> 100$   | < 0,011                     | 100/t<br>1,0                                        |   |
| Eye IR                  | $E_{IR} = \sum E_\lambda \cdot \Delta\lambda$                                      | 780 – 3000          | $\leq 1000$<br>$> 1000$ | 1,4 (80)                    | $18000/t^{0,75}$<br>100                             |   |
| Skin thermal            | $E_H = \sum E_\lambda \cdot \Delta\lambda$                                         | 380 – 3000          | < 10                    | $2\pi$ sr                   | $20000/t^{0,75}$                                    |   |

| <b>Table 5.5</b>                       | Summary of the ELs for the retina (radiance based values)      |                     |                                                  |                                                                        |                                                                    | P |
|----------------------------------------|----------------------------------------------------------------|---------------------|--------------------------------------------------|------------------------------------------------------------------------|--------------------------------------------------------------------|---|
| Hazard Name                            | Relevant equation                                              | Wavelength range nm | Exposure duration sec                            | Field of view radians                                                  | EL in terms of constant radiance $W \cdot m^{-2} \cdot sr^{-1}$    |   |
| Blue light                             | $L_B = \sum L_\lambda \cdot B(\lambda) \cdot \Delta\lambda$    | 300 – 700           | 0,25 – 10<br>10-100<br>100-10000<br>$\geq 10000$ | $0,011 \cdot \sqrt{(t/10)}$<br>0,011<br>$0,0011 \cdot \sqrt{t}$<br>0,1 | $10^6/t$<br>$10^6/t$<br>$10^6/t$<br>100                            |   |
| Retinal thermal                        | $L_R = \sum L_\lambda \cdot R(\lambda) \cdot \Delta\lambda$    | 380 – 1400          | < 0,25<br>0,25 – 10                              | 0,0017<br>$0,011 \cdot \sqrt{(t/10)}$                                  | $50000/(\alpha \cdot t^{0,25})$<br>$50000/(\alpha \cdot t^{0,25})$ |   |
| Retinal thermal (weak visual stimulus) | $L_{IR} = \sum L_\lambda \cdot R(\lambda) \cdot \Delta\lambda$ | 780 – 1400          | > 10                                             | 0,011                                                                  | $6000/\alpha$                                                      |   |

**IEC 62471**

| Clause | Requirement + Test | Result – Remark | Verdict |
|--------|--------------------|-----------------|---------|
|--------|--------------------|-----------------|---------|


| <b>Table 6.1</b>                                                                                                                                          | Emission limits for risk groups of continuous wave lamps |           |                                |                      |        |                |        |                | N/A    |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------|-----------|--------------------------------|----------------------|--------|----------------|--------|----------------|--------|
| Risk                                                                                                                                                      | Action spectrum                                          | Symbol    | Units                          | Emission Measurement |        |                |        |                |        |
|                                                                                                                                                           |                                                          |           |                                | Exempt               |        | Low risk       |        | Mod risk       |        |
|                                                                                                                                                           |                                                          |           |                                | Limit                | Result | Limit          | Result | Limit          | Result |
| Actinic UV                                                                                                                                                | $S_{UV}(\lambda)$                                        | $E_s$     | $W \cdot m^{-2}$               | 0,001                | ---    | 0,003          | ---    | 0,03           | ---    |
| Near UV                                                                                                                                                   |                                                          | $E_{UVA}$ | $W \cdot m^{-2}$               | 10                   | ---    | 33             | ---    | 100            | ---    |
| Blue light                                                                                                                                                | $B(\lambda)$                                             | $L_B$     | $W \cdot m^{-2} \cdot sr^{-1}$ | 100                  | ---    | 10000          | ---    | 4000000        | ---    |
| Blue light, small source                                                                                                                                  | $B(\lambda)$                                             | $E_B$     | $W \cdot m^{-2}$               | 1,0*                 | ---    | 1,0            | ---    | 400            | ---    |
| Retinal thermal                                                                                                                                           | $R(\lambda)$                                             | $L_R$     | $W \cdot m^{-2} \cdot sr^{-1}$ | $28000/\alpha$       | ---    | $28000/\alpha$ | ---    | $71000/\alpha$ | ---    |
| Retinal thermal, weak visual stimulus**                                                                                                                   | $R(\lambda)$                                             | $L_{IR}$  | $W \cdot m^{-2} \cdot sr^{-1}$ | $6000/\alpha$        | ---    | $6000/\alpha$  | ---    | $6000/\alpha$  | ---    |
| IR radiation, eye                                                                                                                                         |                                                          | $E_{IR}$  | $W \cdot m^{-2}$               | 100                  | ---    | 570            | ---    | 3200           | ---    |
| * Small source defined as one with $\alpha < 0,011$ radian. Averaging field of view at 10000 s is 0,1 radian.<br>** Involves evaluation of non-GLS source |                                                          |           |                                |                      |        |                |        |                |        |

| IEC 62471 B ATTACHMENT                                                                                                                                        |                                                                                                                              |  |                        |         |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------|--|------------------------|---------|
| Clause                                                                                                                                                        | Requirement + Test                                                                                                           |  | Result – Remark        | Verdict |
| <b>ATTACHMENT TO TEST REPORT IEC 62471</b><br><b>EUROPEAN GROUP DIFFERENCES AND NATIONAL DIFFERENCES</b><br>Photobiological safety of lamps and lamps systems |                                                                                                                              |  |                        |         |
| Differences according to .....                                                                                                                                | EN 62471:2008                                                                                                                |  |                        |         |
| Annex Form No. ....                                                                                                                                           | EU_GD_IEC62471B                                                                                                              |  |                        |         |
| Annex Form Originator.....                                                                                                                                    | OVE                                                                                                                          |  |                        |         |
| Master Annex Form .....                                                                                                                                       | 2019-01-24                                                                                                                   |  |                        |         |
| Copyright © 2019 IEC System for Conformity Testing and Certification of Electrical Equipment (IECEE), Geneva, Switzerland. All rights reserved.               |                                                                                                                              |  |                        |         |
|                                                                                                                                                               | CENELEC COMMON MODIFICATIONS                                                                                                 |  |                        | P       |
| 4                                                                                                                                                             | EXPOSURE LIMITS                                                                                                              |  |                        | P       |
|                                                                                                                                                               | Contents of the whole Clause 4 of IEC 62471:2006 moved into a new informative Annex ZB                                       |  |                        | P       |
|                                                                                                                                                               | Clause 4 replaced by the following:                                                                                          |  |                        | P       |
|                                                                                                                                                               | Limits of the Artificial Optical Radiation Directive (2006/25/EC) have been applied instead of those fixed in IEC 62471:2006 |  | See appended Table 6.1 | P       |
| 4.1                                                                                                                                                           | General                                                                                                                      |  |                        | P       |
|                                                                                                                                                               | First paragraph deleted                                                                                                      |  |                        | P       |


| Table 6.1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                   | Emission limits for risk groups of continuous wave lamps<br>(Model: CX1558)( $\alpha=0,0105\text{rad}$ , tesd distance = 200,0mm) |                              |                                               |         |                 |          |                 | P      |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|-----------------------------------------------------------------------------------------------------------------------------------|------------------------------|-----------------------------------------------|---------|-----------------|----------|-----------------|--------|
| Risk                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | Action spectrum   | Symbol                                                                                                                            | Units                        | Emission Measurement                          |         |                 |          |                 |        |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                   |                                                                                                                                   |                              | Exempt                                        |         | Low risk        |          | Mod risk        |        |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                   |                                                                                                                                   |                              | Limit                                         | Result  | Limit           | Result   | Limit           | Result |
| Actinic UV                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | $S_{UV}(\lambda)$ | $E_s$                                                                                                                             | $W\cdot m^{-2}$              | 0,001                                         | -       | 0,003           | 4,58e-6  | 0,03            | -      |
| Near UV                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                   | $E_{UVA}$                                                                                                                         | $W\cdot m^{-2}$              | 0,33                                          | -       | 33              | 8,512e-6 | 100             | -      |
| Blue light                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | $B(\lambda)$      | $L_B$                                                                                                                             | $W\cdot m^{-2}\cdot sr^{-1}$ | 1,00e2                                        | -       | 1,00e4          | 1,953e1  | 4,00e6          | -      |
| Blue light, small source                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | $B(\lambda)$      | $E_B$                                                                                                                             | $W\cdot m^{-2}$              | 0,01                                          | -       | 1,0             | 1,303e-2 | 400             | -      |
| Retinal thermal                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | $R(\lambda)$      | $L_R$                                                                                                                             | $W\cdot m^{-2}\cdot sr^{-1}$ | 28000/ $\alpha$                               | -       | 28000/ $\alpha$ | 6,667e2  | 71000/ $\alpha$ | -      |
| Retinal thermal, weak visual stimulus**                                                                                                                                                                                                                                                                                                                                                                                                                                                    | $R(\lambda)$      | $L_{IR}$                                                                                                                          | $W\cdot m^{-2}\cdot sr^{-1}$ | 545000<br>$0,0017\leq \alpha \leq 0,011$      | 2,464e0 |                 |          |                 |        |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                   |                                                                                                                                   |                              | 6000/ $\alpha$<br>$0,011\leq \alpha \leq 0,1$ | -       |                 |          |                 |        |
| IR radiation, eye                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                   | $E_{IR}$                                                                                                                          | $W\cdot m^{-2}$              | 100                                           | -       | 570             | 1,667e-3 | 3200            | -      |
| <div>* Small source defined as one with <math>\alpha &lt; 0,011</math> radian. Averaging field of view at 10000 s is 0,1 radian.</div> <div>** Involves evaluation of non-GLS source</div> <div>NOTE The action functions: see Table 4.1 and Table 4.2</div> <div>The applicable aperture diameters: see 4.2.1</div> <div>The limitations for the angular subtenses: see 4.2.2</div> <div>The related measurement condition 5.2.3 and the range of acceptance angles: see Table 5.5.</div> |                   |                                                                                                                                   |                              |                                               |         |                 |          |                 |        |

**ANNEX 1: Test result in graphical presentation**

Spectral Distribution (200nm-400nm)  
 $E_s = 4,585e-6 \text{ W/m}^2$



Spectral Distribution (315nm-400nm)  
 $E_{uva} = 8,512e-6 \text{ W/m}^2$



### ANNEX 1: Test result in graphical presentation


Spectral Distribution (300nm-700nm)

$E_b = 1,303e-2 \text{ W/m}^2$

$L_b(100\text{mrad}) = 4,900e-1 \text{ W/m}^2/\text{sr}$

$L_b(11\text{mrad}) = 1,953e1 \text{ W/m}^2/\text{sr}$

$L_b(1,7\text{mrad}) = 3,297e1 \text{ W/m}^2/\text{sr}$




Spectral Distribution (380nm-1400nm)

$L_{ir} = 2,464e0 \text{ W/m}^2/\text{sr}$

$L_r(100\text{mrad}) = 6,667e2 \text{ W/m}^2/\text{sr}$

$L_r(11\text{mrad}) = 6,667e2 \text{ W/m}^2/\text{sr}$

$L_r(1,7\text{mrad}) = 1,125e3 \text{ W/m}^2/\text{sr}$




### ANNEX 1: Test result in graphical presentation

Spectral Distribution (380nm-3000nm)

Eir = 1,667e-3 W/m<sup>2</sup>/sr

Eh = 1,710e-1 W/m<sup>2</sup>/sr



### Color parameters

Chromaticity Coordinate: x=0.4871 y=0.4562/u'=0.2598 v'=0.5474

Tc=2679K

Dominant WL: Ld=580.8nm

Peak WL: Lp=585.0nm

Purity=83.2%


Red Ratio: R=23.0%

Render Index: Ra=60.5

FWHM=110.1nm

|        |         |        |        |        |        |        |        |
|--------|---------|--------|--------|--------|--------|--------|--------|
| Ri:    | R1 =53  | R2 =71 | R3 =89 | R4 =53 | R5 =49 | R6 =56 | R7 =79 |
| R8 =33 | R9 =-60 | R10=34 | R11=38 | R12=12 | R13=55 | R14=93 | R15=46 |

**ANNEX 2: Photo document**



**List of test equipment used:**

| No. | Measuring Equipment                  | Model    | Equipment ID | Next Calibration Date | Testing Use |
|-----|--------------------------------------|----------|--------------|-----------------------|-------------|
| 1   | Optical Radiation Safety Test System | OST-500  | FTS-124      | 2026-12-28            | √           |
| 2   | Pupil Imaging Radiance Meter         | CX-2K    | FTS-126      | 2026-12-28            | √           |
| 3   | UV-VIS-near IR Spectrophotometer     | PMS-2000 | FTS-127      | 2026-12-28            | √           |
| 4   | AC Testing Power Source              | DPS1020  | FTS-119      | 2026-05-29            |             |
| 5   | Digital CC&CV DC Power Supply        | WY3010   | FTS-128      | 2026-12-17            |             |
| 6   | Digital power meter                  | WT310    | FTS-123      | 2026-12-17            |             |

——END OF THE REPORT——