



TEST REPORT

Report No.: CCI260600293EN-2R1

Report Date: Jun. 25, 2026

Page 1 of 3

Applicant : Mid Ocean Brands B.V.

Address : Unit 711 716, 7/F., Tower A, 83 King Lam Street, Cheung Sha Wan, Kowloon, Hong Kong.

(The following sample(s) was (were) submitted and identified by client as)

Sample Name : Lithium Battery

Model/Item No. : 30mAh 450909

Test Period : From Jun. 01, 2026 to Jun. 04, 2026

Report Revise Date : Jun. 15, 2026

Tests Conducted : As requested by the applicant, for details refer to attached page(s).

Executive Summary:

No.	TESTED SAMPLE	STANDARD	CONCLUSION
1	Tested material(s) of submitted sample(s)	REGULATION (EU) 2023/1542 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 12 July 2023 concerning batteries and waste batteries - Lead, Cadmium and Mercury	PASS

Signed for and on behalf of

Compliance Control Institute (Guangzhou) Co., Ltd.

Approved by: _____

Pascal SHI/Technical Director

Compliance Control Institute (Guangzhou) Co., Ltd.

Room 701, Building 2, No.89, Majun Street, Nansha District Guangzhou
Guangdong, China
Tel: +86-20-84900678 Fax: +86-20-84910993
Email: cs@ccilab.com.cn Website: www.ccilab.com.cn

This report is governed by, and incorporates by reference, the General Terms and Conditions of Testing which could be obtained / consulted by request to CCI or via the webpage of Conditions of Testing in the official website: www.ccilab.com.cn. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. This report sets forth our findings solely respect to the client's request(s) and the test results are obtained just with the submitted sample identified herein. The test results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. This report can not be reproduced except in full, without prior written permission of CCI. Any unauthorized alteration, forgery or falsification of the content or appearance of this report is unlawful, and any offenders may be prosecuted to the fullest extent of the law.



TEST REPORT

Report No.: CCI260600293EN-2R1

Report Date: Jun. 25, 2026

Page 2 of 3

TESTS CONDUCTED:

1. Lead, Cadmium, Mercury content

Test Method: with reference to IEC 62321-4:2013+A1:2017, IEC 62321-5:2013, was analyzed by Inductively Coupled Plasma Optical Emission Spectroscopy (ICP-OES).

Substances	Pb	Cd	Hg	Conclusion
Limit (%) [#]	0.01	0.002	0.0005	
RL (%)	0.0010	0.0002	0.0002	
Material No.	Result (%)			PASS
1	N.D.	N.D.	N.D.	

Note:

1. % = Percentage by weight.
2. RL = Report limit.
3. N.D. = Not Detected (Less than RL).
4. The test results shown of Cadmium, Mercury and Lead Content are calculated based on the total weight of the battery sample
5. All batteries, accumulators and battery packs should be appropriately marked with the symbol shown as below.
6. # = The requirement of Lead content is applied to the portable batteries, whether or not incorporated into appliances; The requirement of Cadmium content is applied to the portable batteries, whether or not incorporated into appliances, light means of transport or other vehicles; And the requirement of Mercury content is the batteries, whether or not incorporated into appliances, light means of transport or other vehicles.
7. All batteries containing more than 0.002% cadmium or more than 0.004% lead, shall be marked with the chemical symbol for the metal concerned: Cd or Pb. The symbol indicating the heavy metal content shall be printed beneath the symbol shown as below and shall cover an area of at least one quarter the size of that symbol





TEST REPORT

Report No.: CCI260600293EN-2R1


Report Date: Jun. 25, 2026

Page 3 of 3

Test Material List

Material No.	Description
1	Battery (whole)

Test Photo Appendix



Remark: This report replaces CCI260600293EN-2 which will be automatically nullified on the date of issuance of this report.

★★★★★End of Report★★★★★



TEST REPORT

Report No.: CCI260600293EN-1R1

Report Date: Jun. 25, 2026

Page 1 of 3

Applicant : Mid Ocean Brands B.V.

Address : Unit 711 716, 7/F., Tower A, 83 King Lam Street, Cheung Sha Wan, Kowloon, Hong Kong.

(The following sample(s) was (were) submitted and identified by client as)

Sample Name : Lithium Battery

Model/Item No. : 200mAh 601230

Test Period : From Jun. 01, 2026 to Jun. 04, 2026

Report Revise Date : Jun. 15, 2026

Tests Conducted : As requested by the applicant, for details refer to attached page(s).

Executive Summary:

No.	TESTED SAMPLE	STANDARD	CONCLUSION
1	Tested material(s) of submitted sample(s)	REGULATION (EU) 2023/1542 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 12 July 2023 concerning batteries and waste batteries - Lead, Cadmium and Mercury	PASS

Signed for and on behalf of

Compliance Control Institute (Guangzhou) Co., Ltd.

Approved by: _____

Pascal SHI/Technical Director

Compliance Control Institute (Guangzhou) Co., Ltd.

Room 701, Building 2, No.89, Majun Street, Nansha District Guangzhou Guangdong, China
Tel: +86-20-84900678 Fax: +86-20-84910993
Email: cs@ccilab.com.cn Website: www.ccilab.com.cn

This report is governed by, and incorporates by reference, the General Terms and Conditions of Testing which could be obtained / consulted by request to CCI or via the webpage of Conditions of Testing in the official website: www.ccilab.com.cn. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. This report sets forth our findings solely respect to the client's request(s) and the test results are obtained just with the submitted sample identified herein. The test results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. This report can not be reproduced except in full, without prior written permission of CCI. Any unauthorized alteration, forgery or falsification of the content or appearance of this report is unlawful, and any offenders may be prosecuted to the fullest extent of the law.



TEST REPORT

Report No.: CCI260600293EN-1R1

Report Date: Jun. 25, 2026

Page 2 of 3

TESTS CONDUCTED:

1. Lead, Cadmium, Mercury content

Test Method: with reference to IEC 62321-4:2013+A1:2017, IEC 62321-5:2013, was analyzed by Inductively Coupled Plasma Optical Emission Spectroscopy (ICP-OES).

Substances	Pb	Cd	Hg	Conclusion
Limit (%) [#]	0.01	0.002	0.0005	
RL (%)	0.0010	0.0002	0.0002	
Material No.	Result (%)			PASS
1	N.D.	N.D.	N.D.	

Note:

1. % = Percentage by weight.
2. RL = Report limit.
3. N.D. = Not Detected (Less than RL).
4. The test results shown of Cadmium, Mercury and Lead Content are calculated based on the total weight of the battery sample
5. All batteries, accumulators and battery packs should be appropriately marked with the symbol shown as below.
6. # = The requirement of Lead content is applied to the portable batteries, whether or not incorporated into appliances; The requirement of Cadmium content is applied to the portable batteries, whether or not incorporated into appliances, light means of transport or other vehicles; And the requirement of Mercury content is the batteries, whether or not incorporated into appliances, light means of transport or other vehicles.
7. All batteries containing more than 0.002% cadmium or more than 0.004% lead, shall be marked with the chemical symbol for the metal concerned: Cd or Pb. The symbol indicating the heavy metal content shall be printed beneath the symbol shown as below and shall cover an area of at least one quarter the size of that symbol





TEST REPORT

Report No.: CCI260600293EN-1R1

Report Date: Jun. 25, 2026

Page 3 of 3

Test Material List

Material No.	Description
1	Battery (whole)

Test Photo Appendix



Remark: This report replaces CCI260600293EN-1 which will be automatically nullified on the date of issuance of this report.

★★★★★End of Report★★★★★



**TEST REPORT
IEC 62133-2**

**Secondary cells and batteries containing alkaline or other non-acid electrolytes –
Safety requirements for portable sealed secondary cells, and for batteries made
from them, for use in portable applications-**

Part 2: Lithium systems

Report Number.....: NTT26240181B06-1

Date of issue.....: 2026-07-29

Total number of pages.....: 24 pages

Testing Laboratory.....: Guangdong NTT Testing Technology Co., Ltd.

Address.....: Room 201, Building 1, No. 11, Shimenqian Street, Wentang,
Dongcheng, Dongguan City, Guangdong Province, China

Applicant's name.....:

Address.....:

Test specification:

Standard.....: IEC 62133-2:2017+AMD1:2021

Test procedure.....: Test Report

Non-standard test method.....: N/A

TRF template used.....: IECEE OD-2020-F1:2024, Ed.1.7

Test Report Form No.....: IEC62133_2C

Test Report Form(s) Originator.....: DEKRA Certification B.V.

Master TRF.....: Dated 2025-09-26

**Copyright © 2025 IEC System of Conformity Assessment Schemes for Electrotechnical Equipment
and Components (IECEE System). All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the IECEE is acknowledged as copyright owner and source of the material. IECEE takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

**This report is not valid as a CB Test Report unless signed by an approved IECEE Testing Laboratory
and appended to a CB Test Certificate issued by an NCB in accordance with IECEE 02.**

**The results detailed in this test report relate only to the specific sample(s) tested. This report is not
to be reproduced except in full, without written approval from NTT Testing Technology.**



Test item description.....:	Polymer Li-ion Cell	
Trade Mark.....:	N/A	
Manufacturer.....:	Same as applicant	
Address.....:	Same as applicant	
Model/Type reference.....:	450909	
Ratings.....:	3.7V, 30mAh, 0.111Wh	
Responsible Testing Laboratory (as applicable), testing procedure and testing location(s):		
☒ Testing Laboratory:	Guangdong NTT Testing Technology Co., Ltd.	
Testing location/ address.....:	Room 201, Building 1, No. 11, Shimenqian Street, Wentang, Dongcheng, Dongguan City, Guangdong Province, China	
Tested by (name, signature).....:	Miller Gao	<i>Miller Gao</i>
Reviewed By (name, signature).....:	King Chen	<i>King Chen</i>
Approved by (name, signature).....:	Eason Zhou	<i>Eason Zhou</i>
☐ Testing procedure: CTF Stage 1:		
Testing location/ address.....:		
Tested by (name, signature).....:		
Approved by (name, signature).....:		
☐ Testing procedure: CTF Stage 2:		
Testing location/ address.....:		
Tested by (name + signature).....:		
Witnessed by (name, signature).....:		
Approved by (name, signature).....:		
☐ Testing procedure: CTF Stage 3:		
☐ Testing procedure: CTF Stage 4:		
Testing location/ address.....:		
Tested by (name, signature).....:		
Witnessed by (name, signature).....:		
Approved by (name, signature).....:		
Supervised by (name, signature).....:		





List of Attachments:

Appendix 1: 1 page of Photo Documentation

Summary of testing:

Tests performed (name of test and test clause):

cl.7.1 Charging procedure for test purposes (for Cells);
cl.7.2.1 Continuous charging at constant voltage (cells);
cl.7.3.1 External short circuit (cells);
cl.7.3.3 Free fall (cells);
cl.7.3.4 Thermal abuse (cells);
cl.7.3.5 Crush (cells);
cl.7.3.7 Forced discharge (cells);
cl.7.3.9 Design evaluation – Forced internal short circuit (cells)

The electrolyte type of this cell doesn't belong to polymer, and the additional test cl.7.3.9 was carried out to evaluate the cell.

Tests are made with the number of cells specified in IEC 62133-2:2017+AMD1:2021 Table 1.

Testing location:

Guangdong NTT Testing Technology Co., Ltd.
Room 201, Building 1, No. 11, Shimenqian Street,
Wentang, Dongcheng, Dongguan City, Guangdong
Province, China

Summary of compliance with National Differences

N/A

☒ The product fulfils the requirements of EN 62133-2: 2017+A1:2021



Copy of marking plate

The artwork below may be only a draft. The use of certification marks on a product must be authorized by the respective NCBs that own these marks.

- Polymer Li-ion Cell 450909 ICP5/10/10
+ 3.7V 30mAh 0.111Wh YYMMDD

Information for safety mentioned on equipment's package

Potential for fire or burning. Do not disassemble, puncture, crush, heat or burn.

Use only with specified charger.

Keep small cells and batteries which are considered swallowable out of the reach of children.

Swallowing may lead to burns, perforation of soft tissue, and death. Severe burns can occur within 2h of ingestion.

In case of ingestion of a cell or battery, seek medical assistance promptly.

Date code: YYMMDD

"YY" means years, "MM" means month, "DD" means day.

The above markings are the minimum requirements required by the safety standard. For the final production samples, the additional markings which do not give rise to misunderstanding may be added.



Test item particulars..... :	
Classification of installation and use.....:	To be defined in final product
Supply connection.....:	DC electrode tab
Recommend charging method declared by the manufacturer.....:	Charging the cell with 6mA constant current until 4.2V, then constant voltage until charge current reduces to 0.6mA at ambient 20°C±5°C.
Discharge current (0,2 I_t A).....:	6mA
Specified final voltage.....:	3.0V
Upper limit charging voltage per cell.....:	4.2V
Maximum charging current.....:	90mA
Charging temperature upper limit.....:	45°C
Charging temperature lower limit.....:	0°C
Polymer cell electrolyte type.....:	☐ gel polymer ☐ solid polymer ☒ N/A
Possible test case verdicts:	
- test case does not apply to the test object.....:	N/A
- test object does meet the requirement.....:	P (Pass)
- test object does not meet the requirement.....:	F (Fail)
Testing..... :	
Date of receipt of test item.....:	2026-06-10
Date (s) of performance of tests.....:	2026-06-10 to 2026-06-22
General remarks:	
The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the Issuing testing laboratory. "(See Enclosure #)" refers to additional information appended to the report. "(See appended table)" refers to a table appended to the report. Throughout this report a ☐ comma / ☒ point is used as the decimal separator.	
Name and address of factory (ies): Same as applicant	



General product information:

The cell consists of the positive electrode plate, negative electrode plate, separator, electrolyte, case. The positive and negative electrode plates are housed in the case in the state being separated by the separator.


The main features of the cell are shown as below (clause 7.1.1):

Model (Cell)	Nominal capacity	Nominal voltage	Nominal Charge Current	Nominal Discharge Current	Maximum Charge Current	Maximum Discharge Current	Maximum Charge Voltage	Cut-off Voltage
450909	30mAh	3.7V	6mA	6mA	90mA	90mA	4.2V	3.0V

The main features of the cell are shown as below (clause 7.1.2):

Model (Cell)	Upper limit charge voltage	Taper-off current	Lower charge temperature	Upper charge temperature
450909	4.2V	1.5mA	0°C	45°C

Construction:



L: Max.9.8mm, W: Max.9.2mm, T: Max.4.7mm
Cell

Circuit diagram:

None, cell only



IEC 62133-2			
Clause	Requirement + Test	Result - Remark	Verdict
4	PARAMETER MEASUREMENT TOLERANCES		P
	Parameter measurement tolerances		P
5	GENERAL SAFETY CONSIDERATIONS		P
5.1	General		P
	Cells and batteries so designed and constructed that they are safe under conditions of both intended use and reasonably foreseeable misuse		P
5.2	Insulation and wiring		N/A
	The insulation resistance between the positive terminal and externally exposed metal surfaces of the battery (excluding electrical contact surfaces) is not less than 5 MΩ	Cell only.	N/A
	Insulation resistance (MΩ)..... :		—
	Internal wiring and insulation are sufficient to withstand maximum anticipated current, voltage and temperature requirements		N/A
	Orientation of wiring maintains adequate clearances and creepage distances between conductors		N/A
	Mechanical integrity of internal connections accommodates reasonably foreseeable misuse		N/A
5.3	Venting		P
	Battery cases and cells incorporate a pressure relief mechanism or are constructed so that they relieve excessive internal pressure at a value and rate that will preclude rupture, explosion and self-ignition	Venting mechanism exists.	P
	Encapsulation used to support cells within an outer casing does not cause the battery to overheat during normal operation nor inhibit pressure relief		N/A
5.4	Temperature, voltage and current management		N/A
	Batteries are designed such that abnormal temperature rise conditions are prevented	Cell only.	N/A
	Batteries are designed to be within temperature, voltage and current limits specified by the cell manufacturer		N/A
	Batteries are provided with specifications and charging instructions for equipment manufacturers so that specified chargers are designed to maintain charging within the temperature, voltage and current limits specified		N/A
5.5	Terminal contacts		P



IEC 62133-2			
Clause	Requirement + Test	Result - Remark	Verdict
	The size and shape of the terminal contacts ensure that they can carry the maximum anticipated current		P
	External terminal contact surfaces are formed from conductive materials with good mechanical strength and corrosion resistance		P
	Terminal contacts are arranged to minimize the risk of short circuits		P
5.6	Assembly of cells into batteries		N/A
5.6.1	General		N/A
	Each battery has an independent control and protection for current, voltage, temperature and any other parameter required for safety and to maintain the cells within their operating region	Cell only.	N/A
	This protection may be provided external to the battery such as within the charger or the end devices		N/A
	If protection is external to the battery, the manufacturer of the battery provide this safety relevant information to the external device manufacturer for implementation		N/A
	If there is more than one battery housed in a single battery case, each battery has protective circuitry that can maintain the cells within their operating regions		N/A
	Manufacturers of cells specify current, voltage and temperature limits so that the battery manufacturer/designer may ensure proper design and assembly		N/A
	Batteries that are designed for the selective discharge of a portion of their series connected cells incorporate circuitry to prevent operation of cells outside the limits specified by the cell manufacturer		N/A
	Protective circuit components are added as appropriate and consideration given to the end-device application		N/A
	The manufacturer of the battery provide a safety analysis of the battery safety circuitry with a test report including a fault analysis of the protection circuit under both charging and discharging conditions confirming the compliance		N/A
5.6.2	Design recommendation		N/A
	For the battery consisting of a single cell or a single cellblock, it is recommended that the charging voltage of the cell does not exceed the upper limit of the charging voltage specified in Table 2	Cell only.	N/A



IEC 62133-2			
Clause	Requirement + Test	Result - Remark	Verdict
	For the battery consisting of series-connected plural single cells or series-connected plural cellblocks, it is recommended that the voltages of any one of the single cells or single cellblocks does not exceed the upper limit of the charging voltage, specified in Table 2, by monitoring the voltage of every single cell or the single cellblocks		N/A
	For the battery consisting of series-connected plural single cells or series-connected plural cellblocks, it is recommended that charging is stopped when the upper limit of the charging voltage is exceeded for any one of the single cells or single cellblocks by measuring the voltage of every single cell or the single cellblocks		N/A
	For batteries consisting of series-connected cells or cell blocks, nominal charge voltage are not counted as an overcharge protection		N/A
	For batteries consisting of series-connected cells or cell blocks, cells have closely matched capacities, be of the same design, be of the same chemistry and be from the same manufacturer		N/A
	It is recommended that the cells and cell blocks are not discharged beyond the cell manufacturer's specified final voltage		N/A
	For batteries consisting of series-connected cells or cell blocks, cell balancing circuitry are incorporated into the battery management system		N/A
5.6.3	Mechanical protection for cells and components of batteries	Cell only.	N/A
	Mechanical protection for cells, cell connections and control circuits within the battery are provided to prevent damage as a result of intended use and reasonably foreseeable misuse		N/A
	The mechanical protection can be provided by the battery case or it can be provided by the end product enclosure for those batteries intended for building into an end product		N/A
	The battery case and compartments housing cells are designed to accommodate cell dimensional tolerances during charging and discharging as recommended by the cell manufacturer		N/A
	For batteries intended for building into a portable end product, testing with the battery installed within the end product is considered when conducting mechanical tests		N/A
5.7	Quality plan		P



IEC 62133-2			
Clause	Requirement + Test	Result - Remark	Verdict
	The manufacturer prepares and implements a quality plan that defines procedures for the inspection of materials, components, cells and batteries and which covers the whole process of producing each type of cell or battery	Complied. Quality plan provided.	P
5.8	Battery safety components	See TABLE: Critical components information	N/A

6	TYPE TEST AND SAMPLE SIZE		P
	Tests are made with the number of cells or batteries specified in Table 1 using cells or batteries that are not more than six months old		P
	The internal resistance of coin cells are measured in accordance with Annex D. Coin cells with internal resistance less than or equal to 3 Ω are tested in accordance with Table 1	Not coin cells	N/A
	Unless otherwise specified, tests are carried out in an ambient temperature of 20 °C $\pm$ 5 °C		P
	The safety analysis of 5.6.1 identify those components of the protection circuit that are critical for short-circuit, overcharge and over discharge protection	Cell only.	N/A
	When conducting the short-circuit test, consideration is given to the simulation of any single fault condition that is likely to occur in the protecting circuit that would affect the short-circuit test	Cell only.	N/A

7	SPECIFIC REQUIREMENTS AND TESTS		P
7.1	Charging procedure for test purposes		P
7.1.1	First procedure		P
	This charging procedure applies to subclauses other than those specified in 7.1.2		P
	Unless otherwise stated in this document, the charging procedure for test purposes is carried out in an ambient temperature of 20 °C $\pm$ 5 °C, using the method declared by the manufacturer	See page 5.	P
	Prior to charging, the battery has been discharged at 20 °C $\pm$ 5 °C at a constant current of 0,2 It A down to a specified final voltage	See page 5.	P
7.1.2	Second procedure		P
	This charging procedure applies only to 7.3.1, 7.3.4, 7.3.5, and 7.3.9		P



IEC 62133-2			
Clause	Requirement + Test	Result - Remark	Verdict
	After stabilization for 1 h to 4 h, at an ambient temperature of the highest test temperature and the lowest test temperature, respectively, as specified in Table 2, cells are charged by using the upper limit charging voltage and maximum charging current, until the charging current is reduced to 0,05 It A, using a constant current to constant voltage charging method	Charge temperature range: 0-45°C declared. 0°C used for lower limit tests. 45°C used for upper limit tests.	P
7.2	Intended use		P
7.2.1	Continuous charging at constant voltage (cells)		P
	Fully charged cells are subjected for 7 days to a charge using the charging method for current and standard voltage specified by the cell manufacturer	Charging for 7 days with 6mA.	P
	Results: no fire, no explosion, no leakage..... :	(See appended table 7.2.1)	P
7.2.2	Case stress at high ambient temperature (battery)	Cell only.	N/A
	Oven temperature (°C)..... :		—
	Results: no physical distortion of the battery case resulting in exposure of internal protective components and cells		N/A
7.3	Reasonably foreseeable misuse		P
7.3.1	External short-circuit (cell)	Tested complied.	P
	The cells were tested until one of the following occurred:		P
	- 24 hours elapsed; or		N/A
	- The case temperature declined by 20 % of the maximum temperature rise		P
	Results: no fire, no explosion..... :	(See appended table 7.3.1)	P
7.3.2	External short-circuit (battery)	Cell only.	N/A
	The batteries were tested until one of the following occurred:		N/A
	- 24 hours elapsed; or		N/A
	- The case temperature declined by 20 % of the maximum temperature rise		N/A
	In case of rapid decline in short circuit current, the battery pack remained on test for an additional one hour after the current reached a low end steady state condition		N/A
	A single fault in the discharge protection circuit is conducted on one to four (depending upon the protection circuit) of the five samples before conducting the short-circuit test		N/A



IEC 62133-2			
Clause	Requirement + Test	Result - Remark	Verdict
	A single fault applies to protective component parts such as MOSFET (metal oxide semiconductor field-effect transistor), fuse, thermostat or positive temperature coefficient (PTC) thermistor		N/A
	Results: no fire, no explosion.....:		N/A
7.3.3	Free fall	Tested complied.	P
	Results: no fire, no explosion	No fire. No explosion	P
7.3.4	Thermal abuse (cells)	Tested complied.	P
	Oven temperature (°C).....:	130°C	—
	Results: no fire, no explosion	No fire. No explosion	P
7.3.5	Crush (cells)	Tested complied.	P
	The crushing force was released upon:		P
	- The maximum force of 13 kN ± 0,78 kN has been applied; or		P
	- An abrupt voltage drop of one-third of the original voltage has been obtained		N/A
	Results: no fire, no explosion.....:	(See appended table 7.3.5)	P
7.3.6	Over-charging of battery	Cell only.	N/A
	The supply voltage which is:		N/A
	- 1,4 times the upper limit charging voltage presented in Table A.1 (but not to exceed 6,0 V) for single cell/cell block batteries or		N/A
	- 1,2 times the upper limit charging voltage resented in Table A.1 per cell for series connected multi-cell batteries, and		N/A
	- Sufficient to maintain a current of 2,0 It A throughout the duration of the test or until the supply voltage is reached		N/A
	Test was continued until the temperature of the outer casing:		N/A
	- Reached steady state conditions (less than 10 °C change in 30-minute period); or		N/A
	- Returned to ambient		N/A
	Results: no fire, no explosion.....:		N/A
7.3.7	Forced discharge (cells)	Tested complied.	P
	Discharge a single cell to the lower limit discharge voltage specified by the cell manufacturer		P
	The discharged cell is then subjected to a forced discharge at 1 It A to the negative value of the upper limit charging voltage		P



IEC 62133-2			
Clause	Requirement + Test	Result - Remark	Verdict
	- The discharge voltage reaches the negative value of upper limit charging voltage within the testing duration. The voltage is maintained at the negative value of the upper limit charging voltage by reducing the current for the remainder of the testing duration		N/A
	- The discharge voltage does not reach the negative value of upper limit charging voltage within the testing duration. The test is terminated at the end of the testing duration		P
	Results: no fire, no explosion.....:	(See appended table 7.3.7)	P
7.3.8	Mechanical tests (batteries)		N/A
7.3.8.1	Vibration	Cell only.	N/A
	Results: no fire, no explosion, no rupture, no leakage or venting.....:		N/A
7.3.8.2	Mechanical shock	Cell only.	N/A
	Results: no leakage, no venting, no rupture, no explosion and no fire.....:		N/A
7.3.9	Design evaluation – Forced internal short-circuit (cells)	Tested complied.	P
	The cells complied with national requirement for.....:	France, Japan, Republic of Korea, Switzerland	—
	The pressing was stopped upon:		P
	- A voltage drop of 50 mV has been detected; or		N/A
	- The pressing force of 800 N (cylindrical cells) or 400 N (prismatic cells) has been reached	400N for prismatic cells.	P
	Results: no fire.....:	(See appended table 7.3.9)	P

8	INFORMATION FOR SAFETY		P
8.1	General		P
	Manufacturers of secondary cells provides information about current, voltage and temperature limits of their products	Information for safety mentioned in manufacturer's specifications.	P
	Manufacturers of batteries provides information regarding how to minimize and mitigate hazards to equipment manufacturers or end-users		N/A
	Systems analyses are performed by device manufacturers to ensure that a particular battery design prevents hazards from occurring during use of a product		N/A
	As appropriate, any information relating to hazard avoidance resulting from a system analysis is provided to the end user		N/A



IEC 62133-2			
Clause	Requirement + Test	Result - Remark	Verdict
	Do not allow children to replace batteries without adult supervision		N/A
8.2	Small cell and battery safety information	Small cells.	P
	The following warning language is to be provided with the information packaged with the small cells and batteries or equipment using them:		P
	- Keep small cells and batteries which are considered swallowable out of the reach of children		P
	- Swallowing may lead to burns, perforation of soft tissue, and death. Severe burns can occur within 2 h of ingestion		P
	- In case of ingestion of a cell or battery, seek medical assistance promptly		P
9	MARKING		P
9.1	Cell marking		P
	Cells are marked as specified in IEC 61960, except coin cells	The cell is marked in accordance with IEC61960, also see page 4.	P
	Coin cells whose external surface area is too small to accommodate the markings on the cells show the designation and polarity	Not coin cells.	N/A
	By agreement between the cell manufacturer and the battery and/or end product manufacturer, component cells used in the manufacture of a battery need not be marked		N/A
9.2	Battery marking	Cell only.	N/A
	Batteries are marked as specified in IEC 61960, except for coin batteries		N/A
	Coin batteries whose external surface area is too small to accommodate the markings on the batteries show the designation and polarity		N/A
	Batteries are marked with an appropriate caution statement		N/A
	- Terminals have clear polarity marking on the external surface of the battery, or		N/A
	- Not be marked with polarity markings if the design of the external connector prevents reverse polarity connections		N/A
9.3	Caution for ingestion of small cells and batteries		N/A



IEC 62133-2			
Clause	Requirement + Test	Result - Remark	Verdict
	Coin cells and batteries identified as small batteries include a caution statement regarding the hazards of ingestion in accordance with 8.2	Not coin cells	N/A
	Small cells and batteries are intended for direct sale in consumer-replaceable applications, caution for ingestion is given on the immediate package	Not intended for direct sale.	N/A
9.4	Other information		N/A
	The following information are marked on or supplied with the battery:		N/A
	- Storage and disposal instructions		N/A
	- Recommended charging instructions		N/A
10	PACKAGING AND TRANSPORT		N/A
	Packaging for coin cells are not be small enough to fit within the limits of the ingestion gauge of Figure 3		N/A

ANNEX A	CHARGING AND DISCHARGING RANGE OF SECONDARY LITHIUM ION CELLS FOR SAFE USE		P
A.1	General		P
A.2	Safety of lithium ion secondary battery	Complied.	P
A.3	Consideration on charging voltage	Complied.	P
A.3.1	General		P
A.3.2	Upper limit charging voltage	4.2V applied.	P
A.3.2.1	General		P
A.3.2.2	Explanation of safety viewpoint		P
A.3.2.3	Safety requirements, when different upper limit charging voltage is applied	4.2V applied.	P
A.4	Consideration of temperature and charging current		P
A.4.1	General		P
A.4.2	Recommended temperature range	Charging temperature range declared by client is: 0-45°C	P
A.4.2.1	General		P
A.4.2.2	Safety consideration when a different recommended temperature range is applied		P
A.4.3	High temperature range		N/A
A.4.3.1	General		N/A
A.4.3.2	Explanation of safety viewpoint		N/A



IEC 62133-2			
Clause	Requirement + Test	Result - Remark	Verdict
A.4.3.3	Safety considerations when specifying charging conditions in the high temperature range		N/A
A.4.3.4	Safety considerations when specifying a new upper limit in the high temperature range		N/A
A.4.4	Low temperature range		N/A
A.4.4.1	General		N/A
A.4.4.2	Explanation of safety viewpoint		N/A
A.4.4.3	Safety considerations, when specifying charging conditions in the low temperature range		N/A
A.4.4.4	Safety considerations when specifying a new lower limit in the low temperature range		N/A
A.4.5	Scope of the application of charging current		P
A.4.6	Consideration of discharge		P
A.4.6.1	General		P
A.4.6.2	Final discharge voltage and explanation of safety viewpoint	Cell specified final voltage 3.0V, not exceed 3.0V specified by cell manufacturer.	P
A.4.6.3	Discharge current and temperature range		P
A.4.6.4	Scope of application of the discharging current		P
A.5	Sample preparation		P
A.5.1	General		P
A.5.2	Insertion procedure for nickel particle to generate internal short		P
A.5.3	Disassembly of charged cell		P
A.5.4	Shape of nickel particle		P
A.5.5	Insertion of nickel particle in cylindrical cell		N/A
A.5.5.1	Insertion of nickel particle in winding core		N/A
A.5.5.2	Marking the position of the nickel particle on both ends of the winding core of the separator		N/A
A.5.6	Insertion of nickel particle in prismatic cell		P
A.6	Experimental procedure of the forced internal short-circuit test		P
A.6.1	Material and tools for preparation of nickel particle		P
A.6.2	Example of a nickel particle preparation procedure		P
A.6.3	Positioning (or placement) of a nickel particle		P
A.6.4	Damaged separator precaution		P
A.6.5	Caution for rewinding separator and electrode		P



IEC 62133-2			
Clause	Requirement + Test	Result - Remark	Verdict
A.6.6	Insulation film for preventing short-circuit		P
A.6.7	Caution when disassembling a cell		P
A.6.8	Protective equipment for safety		P
A.6.9	Caution in the case of fire during disassembling		P
A.6.10	Caution for the disassembling process and pressing the electrode core		P
A.6.11	Recommended specifications for the pressing device		P
ANNEX B	RECOMMENDATIONS TO EQUIPMENT MANUFACTURERS AND BATTERY ASSEMBLERS		N/A
ANNEX C	RECOMMENDATIONS TO THE END-USERS		N/A
ANNEX D	MEASUREMENT OF THE INTERNAL AC RESISTANCE FOR COIN CELLS		N/A
D.1	General	Not coin cells.	N/A
D.2	Method		N/A
	A sample size of three coin cells is required for this measurement		N/A
	Coin cells with an internal resistance greater than 3 Ω require no further testing..... :		N/A
	Coin cells with an internal resistance less than or equal to 3 Ω are subjected to the testing according to Clause 6 and Table 1		N/A
ANNEX E	PACKAGING AND TRANSPORT		N/A
ANNEX F	COMPONENT STANDARDS REFERENCES		N/A



TABLE: Critical components information					P
Object/part no.	Manufacturer/ trademark	Type/model	Technical data	Standard	Mark(s) of conformity
-Positive electrode	Xiamen Tungsten Industry Co., Ltd.	L700C	Material: LiCoO ₂ , Dimensions: 0.12mm*125mm*10m m	--	--
-Negative electrode	Shenzhen Xinpeng Energy Co., Ltd.	S-11	Material: Graphite or CMC, Super-P, SBR, Dimensions: 0.12mm*138mm*10m m	--	--
-Separator	Shanghai Enjie New Materials Technology Co., Ltd	PE12μm× 11.5mm	Material: PE, Shutdown temperature: 135°C, Thickness: 12μm	--	--
-Electrolyte	Zhuhai Guang Rui New Material Co.,Ltd	GRNLB001	Composition: LiPF ₆ +Solution, Conductivity, (mS/cm):11.6±0.3	--	--
Supplementary information: N/A					



7.2.1	TABLE: Continuous charging at constant voltage (cells)				P
Sample no.	Recommended charging voltage Vc (Vdc)	Recommended charging current I _{rec} (A)	OCV before test(Vdc)	Results	
NTT26240181-C01#	4.20	0.006	4.17	P	
NTT26240181-C02#	4.20	0.006	4.16	P	
NTT26240181-C03#	4.20	0.006	4.17	P	
NTT26240181-C04#	4.20	0.006	4.16	P	
NTT26240181-C05#	4.20	0.006	4.17	P	
Supplementary information: - No fire or explosion - No leakage					

7.3.1	TABLE: External short-circuit (cell)				P
Sample no.	Ambient T (°C)	OCV before test (Vdc)	Resistance of circuit (mΩ)	Maximum case temperature rise ΔT (°C)	Results
Samples charged at charging temperature upper limit (45°C)					
NTT26240181-C06#	55.4	4.17	85.3	110.4	P
NTT26240181-C07#	55.4	4.16	84.9	111.3	P
NTT26240181-C08#	55.4	4.17	84.0	114.7	P
NTT26240181-C09#	55.4	4.16	85.0	115.9	P
NTT26240181-C10#	55.4	4.16	85.5	114.0	P
Samples charged at charging temperature lower limit (0°C)					
NTT26240181-C11#	55.3	4.13	85.2	113.3	P
NTT26240181-C12#	55.3	4.13	84.2	117.3	P
NTT26240181-C13#	55.3	4.14	85.9	117.6	P
NTT26240181-C14#	55.3	4.14	86.0	116.6	P
NTT26240181-C15#	55.3	4.14	85.0	114.5	P
Supplementary information: - No fire or explosion					



7.3.2	TABLE: External short-circuit (battery)					N/A
Sample no.	Ambient T (°C)	OCV before test (Vdc)	Resistance of circuit (mΩ)	Maximum case temperature rise ΔT (°C)	Component single fault condition	Results
--	--	--	--	--	--	--
--	--	--	--	--	--	--
--	--	--	--	--	--	--
--	--	--	--	--	--	--
--	--	--	--	--	--	--
Supplementary information:						

7.3.5	TABLE: Crush (cells)				P
Sample no.	OCV before test (Vdc)	OCV at removal of crushing force (Vdc)	Maximum force applied to the cell during crush (kN)	Results	
Samples charged at charging temperature upper limit (45°C)					
NTT26240181-C29#	4.17	0.68	12.92	P	
NTT26240181-C30#	4.16	0.52	13.01	P	
NTT26240181-C31#	4.16	0.81	13.00	P	
NTT26240181-C32#	4.17	0.69	13.03	P	
NTT26240181-C33#	4.16	0.74	13.01	P	
Samples charged at charging temperature lower limit (0°C)					
NTT26240181-C34#	4.14	0.48	13.04	P	
NTT26240181-C35#	4.13	0.66	13.05	P	
NTT26240181-C36#	4.13	0.50	13.02	P	
NTT26240181-C37#	4.14	0.48	12.98	P	
NTT26240181-C38#	4.13	0.36	13.06	P	
Supplementary information:					
- No fire or explosion					



7.3.6	TABLE: Over-charging of battery				N/A
Constant charging current (A).....:		--			—
Supply voltage (Vdc).....:		--			—
Sample no.	OCV before charging (Vdc)	Total charging time (minute)	Maximum outer case temperature (°C)	Results	
--	--	--	--	--	
--	--	--	--	--	
--	--	--	--	--	
--	--	--	--	--	
--	--	--	--	--	
Supplementary information:					

7.3.7	TABLE: Forced discharge (cells)				P
Sample no.	OCV before application of reverse charge (Vdc)	Measured reverse charge I_t (A)	Lower limit discharge voltage (Vdc)	Results	
NTT26240181-C39#	3.36	0.03	3.00	P	
NTT26240181-C40#	3.35	0.03	3.00	P	
NTT26240181-C41#	3.35	0.03	3.00	P	
NTT26240181-C42#	3.35	0.03	3.00	P	
NTT26240181-C43#	3.36	0.03	3.00	P	
Supplementary information:					
- No fire or explosion					

7.3.8.1	TABLE: Vibration					N/A
Sample no.	OCV before test (Vdc)	OCV after test (Vdc)	Mass before test (g)	Mass after test(g)	Results	
--	--	--	--	--	--	
--	--	--	--	--	--	
--	--	--	--	--	--	
Supplementary information:						



7.3.8.2	TABLE: Mechanical shock					N/A
Sample no.	OCV before test (Vdc)	OCV after test (Vdc)	Mass before test (g)	Mass after test(g)	Results	
--	--	--	--	--	--	
--	--	--	--	--	--	
--	--	--	--	--	--	
Supplementary information:						


7.3.9	TABLE: Forced internal short circuit (cells)					P
Sample no.	Chamber ambient T (°C)	OCV before test (Vdc)	Particle location ¹⁾	Maximum applied pressure (N)	Results	
Samples charged at charging temperature upper limit (45°C)						
NTT26240181-C44#	45	4.16	1	400	P	
NTT26240181-C45#	45	4.16	1	400	P	
NTT26240181-C46#	45	4.17	1	400	P	
NTT26240181-C47#	45	4.16	1	400	P	
NTT26240181-C48#	45	4.16	1	400	P	
Samples charged at charging temperature lower limit (0°C)						
NTT26240181-C49#	0	4.14	1	400	P	
NTT26240181-C50#	0	4.14	1	400	P	
NTT26240181-C51#	0	4.13	1	400	P	
NTT26240181-C52#	0	4.13	1	400	P	
NTT26240181-C53#	0	4.14	1	400	P	
Supplementary information:						
1)Identify one of the following:						
1: Nickel particle inserted between positive and negative (active material) coated area.						
2: Nickel particle inserted between positive aluminium foil and negative active material coated area.						
- No fire or explosion						




D.2	TABLE: Internal AC resistance for coin cells				N/A
Sample no.	Ambient T (°C)	Store time (h)	Resistance Rac (Ω)	Results ¹⁾	
--	--	--	--	--	
--	--	--	--	--	
--	--	--	--	--	
Supplementary information:					
¹⁾ Coin cells with internal resistance less than or equal to 3 Ω, see test result on corresponding tables					



Appendix 1: Photo Documentation

Details of:	Fig.1–Front view of cell 450909
	 A photograph showing the front view of a small, yellow, rectangular lithium battery cell. The cell is placed on a light blue textured surface next to a black ruler with white markings. The ruler shows measurements in millimeters, with markings for 10, 20, 30, and 40 mm. The cell has two silver-colored terminals on the left side. The text on the cell reads: -LR450909, +3.7V30mAh, 202504.

Details of:	Fig.2–Back view of cell 450909
	 A photograph showing the back view of the same small, yellow, rectangular lithium battery cell. The cell is placed on the same light blue textured surface next to the same black ruler. The text on the back of the cell reads: -LR 450909, +3.7V 30mAh, 0.111Wh/2600002.

---End of Test Report---



TEST REPORT
IEC 62133-2

**Secondary cells and batteries containing alkaline or other non-acid electrolytes –
Safety requirements for portable sealed secondary cells, and for batteries made
from them, for use in portable applications-**

Part 2: Lithium systems

Report Number.....: NTT26240180B06-1

Date of issue.....: 2026-07-29

Total number of pages.....: 28 pages

Testing Laboratory.....: Guangdong NTT Testing Technology Co., Ltd.

Address.....: Room 201, Building 1, No. 11, Shimenqian Street, Wentang,
Dongcheng, Dongguan City, Guangdong Province, China

Applicant's name.....:

Address.....:

Test specification:

Standard.....: IEC 62133-2:2017+AMD1:2021

Test procedure.....: Test Report

Non-standard test method.....: N/A

TRF template used.....: IECEE OD-2020-F1:2024, Ed.1.7

Test Report Form No.....: IEC62133_2C

Test Report Form(s) Originator.....: DEKRA Certification B.V.

Master TRF.....: Dated 2025-09-26

**Copyright © 2025 IEC System of Conformity Assessment Schemes for Electrotechnical Equipment
and Components (IECEE System). All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the IECEE is acknowledged as copyright owner and source of the material. IECEE takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

**This report is not valid as a CB Test Report unless signed by an approved IECEE Testing Laboratory
and appended to a CB Test Certificate issued by an NCB in accordance with IECEE 02.**

**The results detailed in this test report relate only to the specific sample(s) tested. This report is not
to be reproduced except in full, without written approval from NTT Testing Technology.**



Test item description.....:	Li-ion Polymer Battery	
Trade Mark.....:	N/A	
Manufacturer.....:	Same as applicant	
Address.....:	Same as applicant	
Model/Type reference.....:	601230	
Ratings.....:	3.7V, 200mAh, 0.74Wh	
Responsible Testing Laboratory (as applicable), testing procedure and testing location(s):		
☒ Testing Laboratory:	Guangdong NTT Testing Technology Co., Ltd.	
Testing location/ address.....:	Room 201, Building 1, No. 11, Shimenqian Street, Wentang, Dongcheng, Dongguan City, Guangdong Province, China	
Tested by (name, signature).....:	Miller Gao	<i>Miller Gao</i>
Reviewed By (name, signature).....:	King Chen	<i>King Chen</i>
Approved by (name, signature).....:	Eason Zhou	<i>Eason Zhou</i>
☐ Testing procedure: CTF Stage 1:		
Testing location/ address.....:		
Tested by (name, signature).....:		
Approved by (name, signature).....:		
☐ Testing procedure: CTF Stage 2:		
Testing location/ address.....:		
Tested by (name + signature).....:		
Witnessed by (name, signature).....:		
Approved by (name, signature).....:		
☐ Testing procedure: CTF Stage 3:		
☐ Testing procedure: CTF Stage 4:		
Testing location/ address.....:		
Tested by (name, signature).....:		
Witnessed by (name, signature).....:		
Approved by (name, signature).....:		
Supervised by (name, signature).....:		





List of Attachments:

Appendix 1: 3 pages of Photo Documentation

Summary of testing:

Tests performed (name of test and test clause):

cl.7.1 Charging procedure for test purposes (for Cells and Batteries);
cl.7.2.1 Continuous charging at constant voltage (cells);
cl.7.2.2 Case stress at high ambient temperature (batteries)
cl.7.3.1 External short circuit (cells);
cl.7.3.2 External short circuit (batteries);
cl.7.3.3 Free fall (cells and batteries);
cl.7.3.4 Thermal abuse (cells);
cl.7.3.5 Crush (cells);
cl.7.3.6 Over-charging of battery;
cl.7.3.7 Forced discharge (cells);
cl.7.3.8 Mechanical tests (batteries);
cl.7.3.9 Design evaluation – Forced internal short circuit (cells)

The electrolyte type of this cell doesn't belong to polymer, and the additional test cl.7.3.9 was carried out to evaluate the cell.

Tests are made with the number of cells and batteries specified in IEC 62133-2:2017+AMD1:2021 Table 1.

Testing location:

Guangdong NTT Testing Technology Co., Ltd.
Room 201, Building 1, No. 11, Shimenqian Street,
Wentang, Dongcheng, Dongguan City, Guangdong
Province, China

Summary of compliance with National Differences

N/A

☒ The product fulfils the requirements of EN 62133-2: 2017+A1:2021



Copy of marking plate

The artwork below may be only a draft. The use of certification marks on a product must be authorized by the respective NCBs that own these marks.

Li-ion Polymer Battery

Model: 601230 1INP7/13/31

Rated: 3.7V 200mAh 0.74Wh

Red wire: + Black wire: -

YYMM

Information for safety mentioned on equipment's package

Potential for fire or burning. Do not disassemble, puncture, crush, heat or burn.

Use only with specified charger.

Keep small cells and batteries which are considered swallowable out of the reach of children.

Swallowing may lead to burns, perforation of soft tissue, and death. Severe burns can occur within 2h of ingestion.

In case of ingestion of a cell or battery, seek medical assistance promptly.

Date code: YYMM

"YY" means years, "MM" means month.

The above markings are the minimum requirements required by the safety standard. For the final production samples, the additional markings which do not give rise to misunderstanding may be added.



Test item particulars..... :	
Classification of installation and use.....:	To be defined in final product
Supply connection.....:	Lead wire
Recommend charging method declared by the manufacturer.....:	Charging the battery with 40mA constant current until 4.2V, then constant voltage until charge current reduces to 4mA at ambient 20°C±5°C.
Discharge current (0,2 I_A).....:	40mA
Specified final voltage.....:	3.0V
Upper limit charging voltage per cell.....:	4.2V
Maximum charging current.....:	200mA
Charging temperature upper limit.....:	45°C
Charging temperature lower limit.....:	0°C
Polymer cell electrolyte type.....:	☐ gel polymer ☐ solid polymer ☒ N/A
Possible test case verdicts:	
- test case does not apply to the test object.....:	N/A
- test object does meet the requirement.....:	P (Pass)
- test object does not meet the requirement.....:	F (Fail)
Testing..... :	
Date of receipt of test item.....:	2026-06-10
Date (s) of performance of tests.....:	2026-06-10 to 2026-06-22
General remarks:	
The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the Issuing testing laboratory. "(See Enclosure #)" refers to additional information appended to the report. "(See appended table)" refers to a table appended to the report. Throughout this report a ☐ comma / ☒ point is used as the decimal separator.	
Name and address of factory (ies): Same as applicant	



General product information:

This battery is constructed with one lithium-ion cell and has overcharge, over-discharge, over current and short-circuits proof circuit.

The main features of the battery pack are shown as below (clause 7.1.1):

Model (Battery)	Nominal capacity	Nominal voltage	Nominal Charge Current	Nominal Discharge Current	Maximum Charge Current	Maximum Discharge Current	Maximum Charge Voltage	Cut-off Voltage
601230	200mAh	3.7V	40mA	40mA	200mA	200mA	4.2V	3.0V


The main features of the cell in the battery pack are shown as below (clause 7.1.1):

Model (Cell)	Nominal capacity	Nominal voltage	Nominal Charge Current	Nominal Discharge Current	Maximum Charge Current	Maximum Discharge Current	Maximum Charge Voltage	Cut-off Voltage
601230	200mAh	3.7V	40mA	40mA	200mA	200mA	4.2V	3.0V


The main features of the cell in the battery pack are shown as below (clause 7.1.2):

Model (Cell)	Upper limit charge voltage	Taper-off current	Lower charge temperature	Upper charge temperature
601230	4.2V	10mA	0°C	45°C

Construction:




L: Max.30.5mm, W: Max.12.5mm, T: Max.6.1mm
Cell



L: Max.32.5mm, W: Max.12.5mm, T: Max.6.2mm
Battery

Circuit diagram:





IEC 62133-2			
Clause	Requirement + Test	Result - Remark	Verdict
4	PARAMETER MEASUREMENT TOLERANCES		P
	Parameter measurement tolerances		P
5	GENERAL SAFETY CONSIDERATIONS		P
5.1	General		P
	Cells and batteries so designed and constructed that they are safe under conditions of both intended use and reasonably foreseeable misuse		P
5.2	Insulation and wiring		P
	The insulation resistance between the positive terminal and externally exposed metal surfaces of the battery (excluding electrical contact surfaces) is not less than 5 MΩ	No metal surface exists.	N/A
	Insulation resistance (MΩ)..... :		—
	Internal wiring and insulation are sufficient to withstand maximum anticipated current, voltage and temperature requirements		P
	Orientation of wiring maintains adequate clearances and creepage distances between conductors		P
	Mechanical integrity of internal connections accommodates reasonably foreseeable misuse		P
5.3	Venting		P
	Battery cases and cells incorporate a pressure relief mechanism or are constructed so that they relieve excessive internal pressure at a value and rate that will preclude rupture, explosion and self-ignition	Venting mechanism exists.	P
	Encapsulation used to support cells within an outer casing does not cause the battery to overheat during normal operation nor inhibit pressure relief		N/A
5.4	Temperature, voltage and current management		P
	Batteries are designed such that abnormal temperature rise conditions are prevented	Overcharge, overdischarge, over current and short-circuit proof circuit used in this battery. See tests of clause 7.	P
	Batteries are designed to be within temperature, voltage and current limits specified by the cell manufacturer	See above.	P
	Batteries are provided with specifications and charging instructions for equipment manufacturers so that specified chargers are designed to maintain charging within the temperature, voltage and current limits specified	The charging limits specified in the manufacturer's specification.	P
5.5	Terminal contacts		P



IEC 62133-2			
Clause	Requirement + Test	Result - Remark	Verdict
	The size and shape of the terminal contacts ensure that they can carry the maximum anticipated current		P
	External terminal contact surfaces are formed from conductive materials with good mechanical strength and corrosion resistance		P
	Terminal contacts are arranged to minimize the risk of short circuits		P
5.6	Assembly of cells into batteries		P
5.6.1	General		P
	Each battery has an independent control and protection for current, voltage, temperature and any other parameter required for safety and to maintain the cells within their operating region	Protective circuit equipped on battery.	P
	This protection may be provided external to the battery such as within the charger or the end devices		N/A
	If protection is external to the battery, the manufacturer of the battery provide this safety relevant information to the external device manufacturer for implementation		N/A
	If there is more than one battery housed in a single battery case, each battery has protective circuitry that can maintain the cells within their operating regions		N/A
	Manufacturers of cells specify current, voltage and temperature limits so that the battery manufacturer/designer may ensure proper design and assembly	Current, voltage and temperature limits specified by cell manufacturer.	P
	Batteries that are designed for the selective discharge of a portion of their series connected cells incorporate circuitry to prevent operation of cells outside the limits specified by the cell manufacturer		N/A
	Protective circuit components are added as appropriate and consideration given to the end-device application		P
	The manufacturer of the battery provide a safety analysis of the battery safety circuitry with a test report including a fault analysis of the protection circuit under both charging and discharging conditions confirming the compliance	Safety analysis report provided by manufacturer.	P
5.6.2	Design recommendation		P
	For the battery consisting of a single cell or a single cellblock, it is recommended that the charging voltage of the cell does not exceed the upper limit of the charging voltage specified in Table 2	Single cell battery, Max. Charging voltage of cell: 4.2V, not exceed 4.2V specified in Clause 7.1.2, Table 2.	P



IEC 62133-2			
Clause	Requirement + Test	Result - Remark	Verdict
	For the battery consisting of series-connected plural single cells or series-connected plural cellblocks, it is recommended that the voltages of any one of the single cells or single cellblocks does not exceed the upper limit of the charging voltage, specified in Table 2, by monitoring the voltage of every single cell or the single cellblocks		N/A
	For the battery consisting of series-connected plural single cells or series-connected plural cellblocks, it is recommended that charging is stopped when the upper limit of the charging voltage is exceeded for any one of the single cells or single cellblocks by measuring the voltage of every single cell or the single cellblocks		N/A
	For batteries consisting of series-connected cells or cell blocks, nominal charge voltage are not counted as an overcharge protection		N/A
	For batteries consisting of series-connected cells or cell blocks, cells have closely matched capacities, be of the same design, be of the same chemistry and be from the same manufacturer		N/A
	It is recommended that the cells and cell blocks are not discharged beyond the cell manufacturer's specified final voltage	Final voltage of battery: 3.0V, for each cell: 3.0V, not exceed the final voltage specified by cell manufacturer.	P
	For batteries consisting of series-connected cells or cell blocks, cell balancing circuitry are incorporated into the battery management system		N/A
5.6.3	Mechanical protection for cells and components of batteries		P
	Mechanical protection for cells, cell connections and control circuits within the battery are provided to prevent damage as a result of intended use and reasonably foreseeable misuse	Mechanical protection for cell connections and control circuits provided.	P
	The mechanical protection can be provided by the battery case or it can be provided by the end product enclosure for those batteries intended for building into an end product	Build-in batteries, mechanical protection for battery should be provided by end product.	N/A
	The battery case and compartments housing cells are designed to accommodate cell dimensional tolerances during charging and discharging as recommended by the cell manufacturer	To be evaluated in final system.	N/A
	For batteries intended for building into a portable end product, testing with the battery installed within the end product is considered when conducting mechanical tests		N/A
5.7	Quality plan		P



IEC 62133-2			
Clause	Requirement + Test	Result - Remark	Verdict
	The manufacturer prepares and implements a quality plan that defines procedures for the inspection of materials, components, cells and batteries and which covers the whole process of producing each type of cell or battery	Quality plan provided.	P
5.8	Battery safety components	See TABLE: Critical components information	N/A

6	TYPE TEST AND SAMPLE SIZE		P
	Tests are made with the number of cells or batteries specified in Table 1 using cells or batteries that are not more than six months old		P
	The internal resistance of coin cells are measured in accordance with Annex D. Coin cells with internal resistance less than or equal to 3 Ω are tested in accordance with Table 1	Not coin cells	N/A
	Unless otherwise specified, tests are carried out in an ambient temperature of 20 °C $\pm$ 5 °C		P
	The safety analysis of 5.6.1 identify those components of the protection circuit that are critical for short-circuit, overcharge and over discharge protection		P
	When conducting the short-circuit test, consideration is given to the simulation of any single fault condition that is likely to occur in the protecting circuit that would affect the short-circuit test	See clause 7.3.2.	P

7	SPECIFIC REQUIREMENTS AND TESTS		P
7.1	Charging procedure for test purposes		P
7.1.1	First procedure		P
	This charging procedure applies to subclauses other than those specified in 7.1.2		P
	Unless otherwise stated in this document, the charging procedure for test purposes is carried out in an ambient temperature of 20 °C $\pm$ 5 °C, using the method declared by the manufacturer	See page 5.	P
	Prior to charging, the battery has been discharged at 20 °C $\pm$ 5 °C at a constant current of 0,2 It A down to a specified final voltage	See page 5.	P
7.1.2	Second procedure		P
	This charging procedure applies only to 7.3.1, 7.3.4, 7.3.5, and 7.3.9		P



IEC 62133-2			
Clause	Requirement + Test	Result - Remark	Verdict
	After stabilization for 1 h to 4 h, at an ambient temperature of the highest test temperature and the lowest test temperature, respectively, as specified in Table 2, cells are charged by using the upper limit charging voltage and maximum charging current, until the charging current is reduced to 0,05 It A, using a constant current to constant voltage charging method	Charge temperature range: 0-45°C declared. 0°C used for lower limit tests. 45°C used for upper limit tests.	P
7.2	Intended use		P
7.2.1	Continuous charging at constant voltage (cells)		P
	Fully charged cells are subjected for 7 days to a charge using the charging method for current and standard voltage specified by the cell manufacturer	Charging for 7 days with 40mA.	P
	Results: no fire, no explosion, no leakage..... :	(See appended table 7.2.1)	P
7.2.2	Case stress at high ambient temperature (battery)	According to the request from client.	P
	Oven temperature (°C)..... :	70°C	—
	Results: no physical distortion of the battery case resulting in exposure of internal protective components and cells	No physical distortion of the battery casing.	P
7.3	Reasonably foreseeable misuse		P
7.3.1	External short-circuit (cell)	Tested complied.	P
	The cells were tested until one of the following occurred:		P
	- 24 hours elapsed; or		N/A
	- The case temperature declined by 20 % of the maximum temperature rise		P
	Results: no fire, no explosion..... :	(See appended table 7.3.1)	P
7.3.2	External short-circuit (battery)	Tested complied.	P
	The batteries were tested until one of the following occurred:		P
	- 24 hours elapsed; or		N/A
	- The case temperature declined by 20 % of the maximum temperature rise		P
	In case of rapid decline in short circuit current, the battery pack remained on test for an additional one hour after the current reached a low end steady state condition		P
	A single fault in the discharge protection circuit is conducted on one to four (depending upon the protection circuit) of the five samples before conducting the short-circuit test	Single fault conducted on three samples.	P



IEC 62133-2			
Clause	Requirement + Test	Result - Remark	Verdict
	A single fault applies to protective component parts such as MOSFET (metal oxide semiconductor field-effect transistor), fuse, thermostat or positive temperature coefficient (PTC) thermistor	Single fault applies on MOSFET (U2).	P
	Results: no fire, no explosion.....:	(See appended table 7.3.2)	P
7.3.3	Free fall	Tested complied.	P
	Results: no fire, no explosion	No fire. No explosion	P
7.3.4	Thermal abuse (cells)	Tested complied.	P
	Oven temperature (°C).....:	130°C	—
	Results: no fire, no explosion	No fire. No explosion	P
7.3.5	Crush (cells)	Tested complied.	P
	The crushing force was released upon:		P
	- The maximum force of 13 kN ± 0,78 kN has been applied; or		P
	- An abrupt voltage drop of one-third of the original voltage has been obtained		N/A
	Results: no fire, no explosion.....:	(See appended table 7.3.5)	P
7.3.6	Over-charging of battery	Tested complied.	P
	The supply voltage which is:		P
	- 1,4 times the upper limit charging voltage presented in Table A.1 (but not to exceed 6,0 V) for single cell/cell block batteries or	5.88V applied.	P
	- 1,2 times the upper limit charging voltage resented in Table A.1 per cell for series connected multi-cell batteries, and		N/A
	- Sufficient to maintain a current of 2,0 It A throughout the duration of the test or until the supply voltage is reached		P
	Test was continued until the temperature of the outer casing:		P
	- Reached steady state conditions (less than 10 °C change in 30-minute period); or		N/A
	- Returned to ambient		P
	Results: no fire, no explosion.....:	(See appended table 7.3.6)	P
7.3.7	Forced discharge (cells)	Tested complied.	P
	Discharge a single cell to the lower limit discharge voltage specified by the cell manufacturer		P
	The discharged cell is then subjected to a forced discharge at 1 It A to the negative value of the upper limit charging voltage		P



IEC 62133-2			
Clause	Requirement + Test	Result - Remark	Verdict
	- The discharge voltage reaches the negative value of upper limit charging voltage within the testing duration. The voltage is maintained at the negative value of the upper limit charging voltage by reducing the current for the remainder of the testing duration		N/A
	- The discharge voltage does not reach the negative value of upper limit charging voltage within the testing duration. The test is terminated at the end of the testing duration		P
	Results: no fire, no explosion.....:	(See appended table 7.3.7)	P
7.3.8	Mechanical tests (batteries)		P
7.3.8.1	Vibration	Tested complied.	P
	Results: no fire, no explosion, no rupture, no leakage or venting.....:	(See appended table 7.3.8.1)	P
7.3.8.2	Mechanical shock	Tested complied.	P
	Results: no leakage, no venting, no rupture, no explosion and no fire.....:	(See appended table 7.3.8.2)	P
7.3.9	Design evaluation – Forced internal short-circuit (cells)	Tested complied.	P
	The cells complied with national requirement for.....:	France, Japan, Republic of Korea, Switzerland	—
	The pressing was stopped upon:		P
	- A voltage drop of 50 mV has been detected; or		N/A
	- The pressing force of 800 N (cylindrical cells) or 400 N (prismatic cells) has been reached	400N for prismatic cells.	P
	Results: no fire.....:	(See appended table 7.3.9)	P
8	INFORMATION FOR SAFETY		P
8.1	General		P
	Manufacturers of secondary cells provides information about current, voltage and temperature limits of their products	Information for safety mentioned in manufacturer's specifications.	P
	Manufacturers of batteries provides information regarding how to minimize and mitigate hazards to equipment manufacturers or end-users	Information for safety mentioned in manufacturer's specifications.	P
	Systems analyses are performed by device manufacturers to ensure that a particular battery design prevents hazards from occurring during use of a product		N/A
	As appropriate, any information relating to hazard avoidance resulting from a system analysis is provided to the end user		N/A



IEC 62133-2			
Clause	Requirement + Test	Result - Remark	Verdict
	Do not allow children to replace batteries without adult supervision		N/A
8.2	Small cell and battery safety information	Small cells and batteries.	P
	The following warning language is to be provided with the information packaged with the small cells and batteries or equipment using them:		P
	- Keep small cells and batteries which are considered swallowable out of the reach of children		P
	- Swallowing may lead to burns, perforation of soft tissue, and death. Severe burns can occur within 2 h of ingestion		P
	- In case of ingestion of a cell or battery, seek medical assistance promptly		P
9	MARKING		P
9.1	Cell marking		N/A
	Cells are marked as specified in IEC 61960, except coin cells	The final product is battery.	N/A
	Coin cells whose external surface area is too small to accommodate the markings on the cells show the designation and polarity		N/A
	By agreement between the cell manufacturer and the battery and/or end product manufacturer, component cells used in the manufacture of a battery need not be marked		N/A
9.2	Battery marking		P
	Batteries are marked as specified in IEC 61960, except for coin batteries	The battery is marked in accordance with IEC 61960, also see copy of marking plate.	P
	Coin batteries whose external surface area is too small to accommodate the markings on the batteries show the designation and polarity	Not coin battery.	N/A
	Batteries are marked with an appropriate caution statement		P
	- Terminals have clear polarity marking on the external surface of the battery, or	The "Red wire: +" and "Black wire: -" polarity explicitly marked on surface of the battery.	P
	- Not be marked with polarity markings if the design of the external connector prevents reverse polarity connections		N/A
9.3	Caution for ingestion of small cells and batteries		N/A



IEC 62133-2			
Clause	Requirement + Test	Result - Remark	Verdict
	Coin cells and batteries identified as small batteries include a caution statement regarding the hazards of ingestion in accordance with 8.2	Not coin cells	N/A
	Small cells and batteries are intended for direct sale in consumer-replaceable applications, caution for ingestion is given on the immediate package	Not intended for direct sale	N/A
9.4	Other information		P
	The following information are marked on or supplied with the battery:		P
	- Storage and disposal instructions	Information for storage and disposal instructions mentioned in manufacturer's specifications.	P
	- Recommended charging instructions	Information for recommended charging instructions mentioned in manufacturer's specifications.	P

10	PACKAGING AND TRANSPORT		N/A
	Packaging for coin cells are not be small enough to fit within the limits of the ingestion gauge of Figure 3	Not coin cells.	N/A

ANNEX A	CHARGING AND DISCHARGING RANGE OF SECONDARY LITHIUM ION CELLS FOR SAFE USE		P
A.1	General		P
A.2	Safety of lithium ion secondary battery	Complied.	P
A.3	Consideration on charging voltage	Complied.	P
A.3.1	General		P
A.3.2	Upper limit charging voltage	4.2V applied.	P
A.3.2.1	General		P
A.3.2.2	Explanation of safety viewpoint		P
A.3.2.3	Safety requirements, when different upper limit charging voltage is applied	4.2V applied.	P
A.4	Consideration of temperature and charging current		P
A.4.1	General		P
A.4.2	Recommended temperature range	Charging temperature range declared by client is: 0-45°C	P
A.4.2.1	General		P
A.4.2.2	Safety consideration when a different recommended temperature range is applied		P



IEC 62133-2			
Clause	Requirement + Test	Result - Remark	Verdict
A.4.3	High temperature range		N/A
A.4.3.1	General		N/A
A.4.3.2	Explanation of safety viewpoint		N/A
A.4.3.3	Safety considerations when specifying charging conditions in the high temperature range		N/A
A.4.3.4	Safety considerations when specifying a new upper limit in the high temperature range		N/A
A.4.4	Low temperature range		N/A
A.4.4.1	General		N/A
A.4.4.2	Explanation of safety viewpoint		N/A
A.4.4.3	Safety considerations, when specifying charging conditions in the low temperature range		N/A
A.4.4.4	Safety considerations when specifying a new lower limit in the low temperature range		N/A
A.4.5	Scope of the application of charging current		P
A.4.6	Consideration of discharge		P
A.4.6.1	General		P
A.4.6.2	Final discharge voltage and explanation of safety viewpoint	Cell specified final voltage 3.0V, not exceed 3.0V specified by cell manufacturer.	P
A.4.6.3	Discharge current and temperature range		P
A.4.6.4	Scope of application of the discharging current		P
A.5	Sample preparation		P
A.5.1	General		P
A.5.2	Insertion procedure for nickel particle to generate internal short		P
A.5.3	Disassembly of charged cell		P
A.5.4	Shape of nickel particle		P
A.5.5	Insertion of nickel particle in cylindrical cell		N/A
A.5.5.1	Insertion of nickel particle in winding core		N/A
A.5.5.2	Marking the position of the nickel particle on both ends of the winding core of the separator		N/A
A.5.6	Insertion of nickel particle in prismatic cell		P
A.6	Experimental procedure of the forced internal short-circuit test		P
A.6.1	Material and tools for preparation of nickel particle		P
A.6.2	Example of a nickel particle preparation procedure		P



IEC 62133-2			
Clause	Requirement + Test	Result - Remark	Verdict
A.6.3	Positioning (or placement) of a nickel particle		P
A.6.4	Damaged separator precaution		P
A.6.5	Caution for rewinding separator and electrode		P
A.6.6	Insulation film for preventing short-circuit		P
A.6.7	Caution when disassembling a cell		P
A.6.8	Protective equipment for safety		P
A.6.9	Caution in the case of fire during disassembling		P
A.6.10	Caution for the disassembling process and pressing the electrode core		P
A.6.11	Recommended specifications for the pressing device		P
ANNEX B	RECOMMENDATIONS TO EQUIPMENT MANUFACTURERS AND BATTERY ASSEMBLERS		N/A
ANNEX C	RECOMMENDATIONS TO THE END-USERS		N/A
ANNEX D	MEASUREMENT OF THE INTERNAL AC RESISTANCE FOR COIN CELLS		N/A
D.1	General	Not coin cells.	N/A
D.2	Method		N/A
	A sample size of three coin cells is required for this measurement		N/A
	Coin cells with an internal resistance greater than 3 Ω require no further testing..... :		N/A
	Coin cells with an internal resistance less than or equal to 3 Ω are subjected to the testing according to Clause 6 and Table 1		N/A
ANNEX E	PACKAGING AND TRANSPORT		N/A
ANNEX F	COMPONENT STANDARDS REFERENCES		N/A



TABLE: Critical components information					P
Object/part no.	Manufacturer/trademark	Type/model	Technical data	Standard	Mark(s) of conformity
Lead wire	Shenzhen Lichi Electronics Co Ltd	1571	26AWG, 80°C, 30Vac	UL 758	UL E536592
Lead wire (Alternative)	Interchangeable	Interchangeable	26AWG, 80°C, 30Vac	UL 758	UL approved
PCB	Shenzhen Lutongda Technology Co Ltd	LTD-D	V-0, 130°C	UL 796 UL 94	UL E486889
PCB (Alternative)	Interchangeable	Interchangeable	V-0, 130°C	UL 796 UL 94	UL approved
IC (U1)	MaoMing Shi BaiQiang Microelectronics Co., Ltd.	DW01A	Over-charge detection Voltage: $4.28 \pm 0.05V$, Over-discharge detection Voltage: $2.4 \pm 0.1V$, T_{OP} : -40~+85°C	--	Tested with appliance
MOSFET (U2)	MaoMing Shi BaiQiang Microelectronics Co., Ltd.	8205A	$V_{DS}=20V$, $V_{GS}=\pm 12V$, $I_D=5A$	--	Tested with appliance
Cell		601230	3.7V, 200mAh	IEC 62133-2:2017+AMD 1:2021	Tested with appliance
-Positive electrode	GEM (Wuxi) Energy Materials Co., LTD	L-5050	$LiNi_{0.5}Co_{0.2}Mn_{0.3}O_2$	--	--
-Negative electrode	Shenzhen Xinpeng Energy Co., LTD	S-8A	Material: Graphite, C content: $\geq 99.90\%$, Particle size D_{50} (um): 1.5~15.5, Specific surface area (m^2/g): ≤ 2.0 , Tap density (g/cm^3): ≥ 20.7	--	--
-Separator	Huizhou Baisite New energy Co., LTD	PE14	PP/PE, Air permeability ($s/100mL$): 249, Porosity: 40%~60%, Tensile strength (MPa): 170, Shutdown temperature: 130°C	--	--



-Electrolyte	Tianjin Jinniu Power Supply Material Co.,LTD	JN-DZWH-2001	LiPF ₆ (10- 12%, wt), EC (25 30%, wt), DMC (16- 22%, wt), EMC (25-30%, wt). Density(g/cm ³):1.25, Electrolyte Conductivity (mS/cm):8.4	--	--
Supplementary information: N/A					



7.2.1	TABLE: Continuous charging at constant voltage (cells)				P
Sample no.	Recommended charging voltage Vc (Vdc)	Recommended charging current I _{rec} (A)	OCV before test(Vdc)	Results	
NTT26240180-C01#	4.20	0.04	4.17	P	
NTT26240180-C02#	4.20	0.04	4.17	P	
NTT26240180-C03#	4.20	0.04	4.18	P	
NTT26240180-C04#	4.20	0.04	4.17	P	
NTT26240180-C05#	4.20	0.04	4.18	P	
Supplementary information:					
- No fire or explosion					
- No leakage					

7.3.1	TABLE: External short-circuit (cell)				P
Sample no.	Ambient T (°C)	OCV before test (Vdc)	Resistance of circuit (mΩ)	Maximum case temperature rise ΔT (°C)	Results
Samples charged at charging temperature upper limit (45°C)					
NTT26240180-C06#	55.1	4.16	84.1	112.4	P
NTT26240180-C07#	55.1	4.15	83.2	112.5	P
NTT26240180-C08#	55.1	4.15	86.0	110.1	P
NTT26240180-C09#	55.1	4.16	84.6	114.2	P
NTT26240180-C10#	55.1	4.16	84.3	114.6	P
Samples charged at charging temperature lower limit (0°C)					
NTT26240180-C11#	55.3	4.13	83.0	114.2	P
NTT26240180-C12#	55.3	4.12	85.1	117.2	P
NTT26240180-C13#	55.3	4.12	85.6	115.8	P
NTT26240180-C14#	55.3	4.13	80.7	114.7	P
NTT26240180-C15#	55.3	4.12	85.5	116.3	P
Supplementary information:					
- No fire or explosion					



7.3.2	TABLE: External short-circuit (battery)					P
Sample no.	Ambient T (°C)	OCV before test (Vdc)	Resistance of circuit (mΩ)	Maximum case temperature rise ΔT (°C)	Component single fault condition	Results
NTT26240180-B04#	23.3	4.17	85.2	113.3	Short Circuit MOSFET (U2)	P
NTT26240180-B05#	23.3	4.18	83.5	112.4	Short Circuit MOSFET (U2)	P
NTT26240180-B06#	23.3	4.17	80.9	112.9	Short Circuit MOSFET (U2)	P
NTT26240180-B07#	23.3	4.17	83.6	23.5	/	P
NTT26240180-B08#	23.3	4.18	82.8	23.8	/	P
Supplementary information: - No fire or explosion						

7.3.5	TABLE: Crush (cells)				P
Sample no.	OCV before test (Vdc)	OCV at removal of crushing force (Vdc)	Maximum force applied to the cell during crush (kN)	Results	
Samples charged at charging temperature upper limit (45°C)					
NTT26240180-C29#	4.16	4.15	13.01	P	
NTT26240180-C30#	4.15	4.15	12.98	P	
NTT26240180-C31#	4.15	4.14	12.95	P	
NTT26240180-C32#	4.16	4.16	13.06	P	
NTT26240180-C33#	4.15	4.15	13.04	P	
Samples charged at charging temperature lower limit (0°C)					
NTT26240180-C34#	4.12	4.11	13.00	P	
NTT26240180-C35#	4.13	4.13	12.98	P	
NTT26240180-C36#	4.13	4.13	12.95	P	
NTT26240180-C37#	4.12	4.12	12.99	P	
NTT26240180-C38#	4.12	4.11	13.00	P	
Supplementary information:					
- No fire or explosion					



7.3.6	TABLE: Over-charging of battery				P
Constant charging current (A).....:			0.40	—	
Supply voltage (Vdc).....:			5.88	—	
Sample no.	OCV before charging (Vdc)	Total charging time (minute)	Maximum outer case temperature (°C)	Results	
NTT26240180-B12#	3.33	71.0	32.8	P	
NTT26240180-B13#	3.33	71.0	34.5	P	
NTT26240180-B14#	3.33	71.0	34.6	P	
NTT26240180-B15#	3.34	71.0	33.8	P	
NTT26240180-B16#	3.34	71.0	33.6	P	
Supplementary information:					
- No fire or explosion					

7.3.7	TABLE: Forced discharge (cells)				P
Sample no.	OCV before application of reverse charge (Vdc)	Measured reverse charge I_t (A)	Lower limit discharge voltage (Vdc)	Results	
NTT26240180-C39#	3.33	0.20	3.00	P	
NTT26240180-C40#	3.32	0.20	3.00	P	
NTT26240180-C41#	3.33	0.20	3.00	P	
NTT26240180-C42#	3.35	0.20	3.00	P	
NTT26240180-C43#	3.35	0.20	3.00	P	
Supplementary information:					
- No fire or explosion					

7.3.8.1	TABLE: Vibration					P
Sample no.	OCV before test (Vdc)	OCV after test (Vdc)	Mass before test (g)	Mass after test (g)	Results	
NTT26240180-B17#	4.18	4.17	4.006	4.005	P	
NTT26240180-B18#	4.18	4.18	3.986	3.986	P	
NTT26240180-B19#	4.17	4.17	3.899	3.897	P	
Supplementary information: - No fire or explosion - No rupture - No leakage - No venting						



7.3.8.2	TABLE: Mechanical shock					P
Sample no.	OCV before test (Vdc)	OCV after test (Vdc)	Mass before test (g)	Mass after test(g)	Results	
NTT26240180-B20#	4.18	4.17	4.009	4.009	P	
NTT26240180-B21#	4.17	4.17	3.993	3.992	P	
NTT26240180-B22#	4.17	4.17	3.964	3.964	P	
Supplementary information: - No fire or explosion - No rupture - No leakage - No venting						

7.3.9	TABLE: Forced internal short circuit (cells)					P
Sample no.	Chamber ambient T (°C)	OCV before test (Vdc)	Particle location ¹⁾	Maximum applied pressure (N)	Results	
Samples charged at charging temperature upper limit (45°C)						
NTT26240180-C44#	45	4.16	1	400	P	
NTT26240180-C45#	45	4.15	1	400	P	
NTT26240180-C46#	45	4.16	1	400	P	
NTT26240180-C47#	45	4.15	1	400	P	
NTT26240180-C48#	45	4.16	1	400	P	
Samples charged at charging temperature lower limit (0°C)						
NTT26240180-C49#	0	4.12	1	400	P	
NTT26240180-C50#	0	4.13	1	400	P	
NTT26240180-C51#	0	4.12	1	400	P	
NTT26240180-C52#	0	4.12	1	400	P	
NTT26240180-C53#	0	4.13	1	400	P	
Supplementary information: ¹⁾ Identify one of the following: 1: Nickel particle inserted between positive and negative (active material) coated area. 2: Nickel particle inserted between positive aluminium foil and negative active material coated area. - No fire or explosion						



D.2	TABLE: Internal AC resistance for coin cells				N/A
Sample no.	Ambient T (°C)	Store time (h)	Resistance Rac (Ω)	Results ¹⁾	
--	--	--	--	--	
--	--	--	--	--	
--	--	--	--	--	
Supplementary information:					
1) Coin cells with internal resistance less than or equal to 3 Ω, see test result on corresponding tables					

Appendix 1

Email: tom@ntt-testing.com



Tel: 86-769-27282005



<http://www.ntt-testing.com>



Add: Room 201, Building 1, No. 11, Shimenqian Street, Wentang, Dongcheng, Dongguan City, Guangdong Province, China



Photo Documentation







---End of Test Report---